The original and first of this report are to filed with the

State Well No.

of this report are to filed with the DEC 17 1968 STATE OF STATE ENGINEER, SALEM, OREGON 97310 (Please typ within 30 days from STATE ENGINEER) (Please typ within 30 days from STATE ENGINEER)	e or print) \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
of well completion. SALEM OREGON	
(1) OWNED.	(11) LOCATION OF WELL:
(1) OWNER: Name Verna Gilliland	County Umatilla Driller's well number
Address R1 B6624 Pregon 71868	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	8"t, 3,18" +1
Potager NG Driven []	(12) WELL LOG: Diameter of well below casing from 3/3/3/4
Cable	Depth drilled 497 ft. Depth of completed well 497 ft.
ASING INSTALLED: Threaded Welded M. # Diam. from ft. to ft. Gage 250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
" Diam. from ft. to ft. Gage	MATERIAL From To SWL
"Diam from ft. to ft. Gage ft. Gage	
Perforated? ☐ Yes ☑ No.	Rock, blacks 17 26
Type of perforator used	2630
Size of perforations in. by in.	Prof. black with life thek 30 65
perforations from ft. to ft.	Rock dach hed 65 97
perforations from ft. to ft.	Rock blacks 77 95
perforations from ft. to ft.	Rock, aray hard 95 105
perforations from ft. to ft.	Shale delack W. fleres 105 110
perforations fromft. toft.	Basaft gray hard 110 150
(7) SCREENS: Well screen installed? Yes You	Brik, Journ 150 175
Manufacturer's Name	Kock Wack
Type Model No.	Sha de Marine Alue 193 200
Diam. Slot size Set from the ft. to ft.	Clay doub from 4 willow 200 224
Diam. Slot size Set from ft. to ft.	Bahack 224260
(8) WATER LEVEL: Completed well.	Pock delack med 260 300
Static level 2C ft. below land surface Date 12-10-68	Basall 300 385
sian pressure lbs. per square inch Date	Publed W. blue shale 385 388
	Reck, dark red 388 391
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	Socia, May 311 920
Was a pump test made? Yes No If yes, by whom?	Technical Health
gal./min. with ft. drawdown after hrs.	Work started 11-221968 Completed 12-10 1968
" " "	Date well drilling machine moved off of well /2 - /0 19 6
auter 15 cget frien 240 ff in "	Drilling Machine Operator's Certification:
Baller test /6 gal./min. with 0 2 ft. drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief.
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	[Signed] July Date 14, 1968
(10) CONSTRUCTION:	Drilling Machine Operator's License No. 15
Well seal-Material used Clinium	
Depth of seal 12 ft.	Water Well Contractor's Certification:
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Were any loose strata cemented off? Yes No Depth	NAME TROY (SE'/F/M) (Person, firm or corporation) (Type or print)
Was a drive shoe used? ✓ Yes □ No	
Did any strata contain unusable water? Yes No	Address 915 HERMISTON AVE, HERMISTON OF
Type of water? depth of strata	Tand Starley
Method of sealing strata off	[Signed] (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	Contractor's License No. 65 Date 12-14 , 1968.
Gravel placed from ft. to ft.	Contractor's License No Date