STATE OF OREGON JUL 1 0 1975 State Well No. 2H -28Enof this report are to be filed with the (Please type or FATER RESOURCES DEPT Permit No. STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date (Do not write above this limeALEM. OREGON of well completion. G-6645 (Eagle Ranch #4 2/28-16dd) (10) LOCATION OF WELL: (1) OWNER: Driller's well number 7 Prov# 4 County Umatilla Brown Don_ SE 14 NW4 Section / T. 2 NR. 28 E Address Star Route Moses LAKE wan 98837 Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Deepening [Reconditioning [Abandon | New Well If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (4) PROPOSED USE (check): (3) TYPE OF WELL: Depth at which water was first found Rotary Driven | ft. below land surface. Date Domestic | Industrial | Municipal | Static level Cable Irrigation 🕱 Test Well 🗌 Other lbs. per square inch. Date - 20. Artesian pressure Bored 🔲 Dug CASING INSTALLED: Threaded | Welded K (12) WELL LOG: Diameter of well below casing . 16 " Diam. from + 1 ft. to 57 ft. Gage 250 ft. Depth of completed well Depth drilled " Diam. from _____ ft. to _____ ft. Gage ___ Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, " Diam. from _____ ft. to ____ ft. Gage ____ with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. PERFORATIONS: Perforated? | Yes | No. MATERIAL Type of perforator used Locar Brown TOP Soil in. by Size of perforations Top Soil & Smell Cohles perforations from ft. to ... Chay, Gravel & Cobbles 6 43 51 perforations from ft. to ... Baselt Brown medium hard 5 ì Basalt gray Black havid 176 (7) SCREENS: 70 Well screen installed? | Yes A No Baselt Black & Brown Manufacturer's Name 192 Rasalt Black hard Basalt Black Soft 220 250 Diam. Slot size Set from Reack hard 250 Diam. Slot size Set from Rlack SOFT Drawdown is amount water level is lowered below static level (8) WELL TESTS: 310 Black Love 346 Blackb Braon Soft Was a pump test made? Yes I No If yes, by whom? Proy Basalt Black Soft Yield: 1600 gal./min. with 40 ft. drawdown after 2 V hrs. 397 hard 462 487 gal./min. with ft. drawdown after hrs. Bailer test rtesian flow 320 g.p.m. Depth artesian flow encountered 535 ft. 1-25 1975 Completed 3perature of water Date well drilling machine moved off of well (9) CONSTRUCTION: Drilling Machine Operator's Certification: Well seal-Material used Meat Cemen This well was constructed under my direct supervision. Well sealed from land surface to ____57__ Materials used and information reported above are true to my best knowledge and belief. Diameter of well bore to bottom of seal (Drilling Machine Operator) Diameter of well bore below seal ______i 2___ in. 20 Number of sacks of cement used in well seal Drilling Machine Operator's License No.755.... Number of sacks of bentonite used in well seal Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Was a drive shoe used? 🗌 Yes ಶ No Plugs Size: location ft. Name Maddox Drilling Did any strata contain unusable water? 🗌 Yes 🖼 No Type of water? depth of strata Method of sealing strata off Was well gravel packed? 🗌 Yes 🔀 No 🛮 Size of gravel: Contractor's License No. 555 Date Gravel placed from ft. to

NOTICE TO WATER WELL CONTRACTOR
The original and first copy

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

UM A TWATER WELL REPORT I VED

STATE OF OREGONUL 1 0 1975

State Well No. 2N -28E

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

add: va

(Please type or print) RESOURCES DEPTstate Permit No.
(Do not write above this line), OREGON

1) OWNER:	(10) LOCAT				Dec.	21- A4
Tame Dan Brown	County		_			
Address		1/4 Section		R		W.M.
The state of the s	Bearing and dis	tance from	section or subdivision	n corner		
	<u>,</u>	<u> 4 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 - 5 -</u>	··			
New Well □ Deepening □ Reconditioning □ Abandon □						· · · · · · ·
of abandonment, describe material and procedure in Item 12.	(11) WATE	R LEVEL	: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which	water was f	rirst found			ft.
Rotary Driven Domestic D Industrial Municipal D	Static level	* 13/1-mm in 1	ft, below land s	urface. I	Date	
Cable	Artesian pressu	re ·	lbs. per squar	e inch.	Date	

CASING INSTALLED: Threaded □ Welded □	(12) WELI	L LOG:	Diameter of well h			
" Diam. from ft. to ft. Gage	Depth drilled		ft. Depth of compl			ft.
" Diam. fromft. toft. Gage	Formation: De	scribe color,	texture, grain size a sture of each stratur	nd struct	ture of m	naterials; netrated,
	with at laget on	a entry for e	ach change of formal	tion. Rep	ort each c	nunye m
PERFORATIONS: Perforated? Yes No.	position of Stat	ic Water Ler	vel and indicate prin	cipai wai	er-oearin	
Type of perforator used		MATERIAI		From	То	SWL
Size of perforations in. by in.	BOSALT	Buckb	Brown SOFT	574		BOJ 6
perforations fromft. toft.	Basat	Beack	hard	624	640	
perforations fromft. toft.						
perforations fromft. toft.						
A state of the sta				-		
(7) SCREENS: Well screen installed? Yes No						
Manufacturer's Name						
Type Model No Slot size Set from ft. to ft.						
Diam. Slot size Set from ft. to ft.						
(8) WELL TESTS: Drawdown is amount water level is lowered below static level					<u> </u>	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?				_	<u> </u>	<u> </u>
the state of the s				ļ	 	
Yield: gal./mm. with it. drawdown after ind.			<u> </u>	<u> </u>	 	
2 15 m				 	+	
7		····		 	 -	
Bailer test gal./min. with ft. drawdown after hrs.				+	 	
Artesian flow g.p.m.			10 Comple	tod		19
perature of water Depth artesian flow encountered ft.	Work started		19 Comple	ieu		19
(9) CONSTRUCTION:	-		moved off of well		<u></u>	
Well seal—Material used	Drilling Mac	chine Opera	ator's Certification	: - 3:	4 41170	nwision
Well sealed from land surface toft.	This we	ell was cons	structed under my formation reported	direc	are tru	e to my
Diameter of well bore to bottom of sealin.	best knowled	dge and bei	ieľ.			
Diameter of well bore below sealin.	[Signed]		Machine Operator)	. Date		, 19
Number of sacks of cement used in well sealsacks	Deilling Mac	abina Onar	ator's License No.			
Number of sacks of bentonite used in well seal sacks	Diffilling Mad	chine Oper	4,07.5 22,001.50			
Brand name of bentonite	Water Well	Contractor'	's Certification:			
Number of pounds of bentonite per 100 gallons	This we	llirh zaw II	ed under my juris	diction	and this	report is
of waterlbs./100 gals.	true to the	best of my	knowledge and b	ener.		
Was a drive shoe used? 🗆 Yes 🗆 No Plugs Size: location ft.	Name	(Person firm	or corporation)	(Type or p	rint)
Did any strata contain unusable water? Yes No						
Type of water? depth of strata	Audress	41	600.	11	1	
Method of sealing strata off	[Signed]	Mar	(Water Well Co	tractor)	<u> </u>	
Was well gravel packed? Yes No Size of gravel:			o. 515 Date	1 -	24	10 つぶ
Gravel placed from ft. to ft.	Contractor's	License N	o. 53.5 Date	¥		, 18 <u></u>