

WATER WELL REPORT
STATE OF OREGON

RECEIVED
OCT 14 1983
WATER RESOURCES DEPT.
SALEM, OREGON

UMAT
4711

State Well No. 6W/35E-270d
State Permit No. Deepening

(1) OWNER:

Name LARRY E HASKAMAN
Address Rt 4 Box 168
City MILTON FREELANDER State OR

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Air Driven
Mud Dug
 Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other
Thermal: Withdrawal ReInjection

(5) CASING INSTALLED:

Steel Plastic
Threaded Welded

6" Diam. from + 1/2 ft. to UNKNOWN Gauge 0.250
" Diam. from " ft. to " ft. Gauge "

LINER INSTALLED:

" Diam. from " ft. to " ft. Gauge "

(6) PERFORATIONS:

Perforated? Yes No

Type of perforator used UNKNOWN
Size of perforations in. by in.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

perforations from " ft. to " ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name

Type Model No.

Diam. Slot Size Set from " ft. to " ft.

Diam. Slot Size Set from " ft. to " ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Is a pump test made? Yes No If yes, by whom?

Field: gal./min. with " ft. drawdown after " hrs.

Air test 40 gal./min. with drill stem at 203 ft. 1 hrs.

Bailer test gal./min. with " ft. drawdown after " hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered " ft.

(9) CONSTRUCTION:

Special standards: Yes No

Well seal—Material used CEMENT

Well sealed from land surface to 1.8 ft.

Diameter of well bore to bottom of seal 1.0 in.

Diameter of well bore below seal 6 in.

Number of sacks of cement used in well seal 10 sacks

How was cement grout placed? PUMPED

Was pump installed? NO Type HP Depth " ft.

Was a drive shoe used? Yes No Plugs Size: location " ft.

Did any strata contain unusable water? Yes No

Type of Water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel: " "

Gravel placed from " ft. to " ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
SE 1/4 SE 1/4 Section 17 T. 6N R. 35E W.M.
Tax Lot # Lot Blk Subdivision

Address at well location: same

(11) WATER LEVEL: Completed well.

Depth at which water was first found " ft.

Static level 30 ft. below land surface. Date 9-21-83

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 205 ft. Depth of completed well 205 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Clay Gravel & Boulder	86	115	
Cement Gravel	115	205	30

Work started 9-20 1983 Completed 9-21 - 1983
Date well drilling machine moved off of well 9-21 - 1983

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Clarence W. Summers Date 10-8, 1983

Bonded Water Well Constructor Certification:

Bond (number) Issued by: Surety Company Name

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name C.W. Summers Well Drilling
(Person, firm or corporation) (Type or print)

Address Rt 3 Box 143-A-1 7749 OR

[Signed] Clarence W. Summers
Water Well Constructor

Date 10-8, 1983

NOTICE TO WATER WELL CONSTRUCTOR
The original and first copy of this report are to be filed with the