

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER WELL REPORT

RECEIVED

6N/35E-28CC

WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON

(Please type or print)

JUL 20 1978

State Well No.

State Permit No.

G-8469?

(Do not write above this line)

WATER RESOURCES DEPT.
SALEM, OREGON

UMAT
4762

(1) OWNER:

Name Loren Vertner
Address 6802 West 10th Kennewick

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Cable Dug
Driven Jetted Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded

0" Diam. from 15 ft. to -18 ft. Gage .250
8" Diam. from 12 ft. to -78 ft. Gage .250
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? Yes No.

Type of perforator used

Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a AIR test made? Yes No If yes, by whom? DRILLER
Yield: 150 gal./min. with 190 ft. drawdown after 1 hrs.

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water 58 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 18 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 7 7/8 in.
Number of sacks of cement used in well seal 7 sacks
How was cement grout placed? GRAVITY IN DRY
HOLE

Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County UMATILLA Driller's well number 85-78
S 1/4 SW 1/4 Section 28 T. 6N R. 35E W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 180 ft.

Static level 93 ft. below land surface. Date 7-10-78

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 7 7/8

Depth drilled 315 ft. Depth of completed well 315 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	14	
CEMENTED GRAVEL	14	45	
RED SAND	45	65	
CEMENTED GRAVEL + Boulder	65	180	
" GRAVEL	180	280	
" GRAVEL H ₂ O	280	290	
" GRAVEL	290	315	

Work started 7-8 1978 Completed 7-10 1978

Date well drilling machine moved off of well 7-10 1978

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Jerry Burd Date 7-10, 1978
(Drilling Machine Operator)

Drilling Machine Operator's License No. 933

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Jerry Burd Well Drilling
(Person, firm or corporation) (Type or print)

Address Pendleton Ore

[Signed] Jerry Burd
(Water Well Contractor)

Contractor's License No. 544 Date 7-10, 1978