NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORTECEIVED

STATE OF OREGON

AUG9 1974 State Well No. 6N/35E-28ac

(Please type or print)

(Do not write above this line)

			-	_							
T.	A	T	Ε	EN	311	NE	Ε	tate	Permit	No.	

	SALEM, OREGON				
(1) OWNER:	(10) LOCATION OF WELL:				
Name Mr Ronald Richman	County Umatilla Driller's well number				
Address	5 AV 14 NOT 14 Section 28 T. 6N R. 35 Ew.M.				
Milton Freewater, Oregon	Bearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):	a sandivisión contes				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	Man and the second seco				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):					
Rotary Driven Domestic X Industrial Municipal D	Depth at which water was first found Static level 20 ft. below land surface. Date 7/5/7				
Cable					
CACINA PARAMANA	Artesian pressure Ibs. per square inch. Date				
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 8				
8 " Diam. from 0 ft. to 50 ft. Gage 0.250	Depth drilled 62 ft. Depth of completed well 62 ft				
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials				
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated				
PERFORATIONS: Perforated? Yes XNo.	with at least one entry for each change of formation. Report each change it position of Static Water Level and indicate principal water-bearing strate				
Type of perforator used	MATERIAL From To SWL				
Size of perforations in. by in.	Soil brown sandy 0 19				
perforations from ft. to ft.	Gravel med & clay 19 48 21				
perforations fromft. toft.	Gravel course 48 56 20				
perforations from ft. to ft.	Gravel med & clay 56 62				
(7) SCREENS: Well screen installed? Yes No					
Manufacturer's Name					
Type Model No					
Diam ft. to ft.	4.				
Diam. Slot size Set from ft. to ft.					
(8) WELL TESTS: Drawdown is amount water level is					
lowered below static level Dullimer's					
Was a pump test made? Yes \(\subseteq \) No If yes, by whom? Drilling					
Yield: 40 gal./min. with 3 ft, drawdown after 22 hrs.	7 4				
" "					
# # # # # # # # # # # # # # # # # # #					
Bailer test gal./min. with ft. drawdown after hrs.	A CANADA				
Artesian flow g.p.m.					
perature of water 56 Depth artesian flow encountered ft.	Work started 6/24/74 19 Completed 7/5/74 19				
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/5/74 19				
Well seal—Material usedBentonite	Drilling Machine Operator's Certification:				
Well sealed from land surface to	This well was constructed under my direct supervision.				
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.				
Diameter of well bore below seal					
Number of sacks of cement used in well seal sacks	[Signed] Machine Operator) (Drilling Machine Operator)				
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 821				
Brand name of bentonite National Lead co	Water Well Contractor's Certification:				
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is				
of water	true to the best of my knowledge and belief.				
Did any strata contain unusable water? Yes A No	Name C.W. Summers Well Drilling (Person, firm or corporation) (Type or print)				
Type of water? depth of strata	(Person, firm or corporation) (Type or print) Address Rt. # 1 Box # 40 Weston, Oregon				
Wethod of sealing strate of	A TON THE TON, Uregon				
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)				
Gravel placed fromft. toft.					
ft.	Contractor's License No. 575 Date 7/15/74 , 19				