NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENTUM AT SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT UMAT 4874 STATE OF OREGON

(Please type or print)
(Do not write above this line)

RECEIVED

State WAR 1 1 1982 6/35-33

WATER REENURCES DEPT SALL..., OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name M.A. Pescialo	County Umatilla Driller's well number			
Address Rt. 2 Box 80	33B T. 6N R. 35 W.			W.M
Milton-Freewater, Or. 97862	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well 1 Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 55			f
Rotary Driven Domestic Industrial Municipal	Static level 55 ft. below land s	urfoce T)nto	
Cable				
2 Date Date	Artesian pressure lbs. per squar	e inch. L	Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well to	elow casi	ng	10"
10 " Diam. from +1 ft. to 56 ft. Gage • 250	Depth drilled 260 ft. Depth of compl			f
8 " Diam. from 50 ft. to 260 ft. Gage PVC	Formation: Describe color, texture, grain size			materials
	and show thickness and nature of each stratu	m and aq	uifer pe	enetrated
, PERFORATIONS: Perforated? F Yes No.	with at least one entry for each change of formal position of Static Water Level and indicate prin			
Type of perforator used Chain saw	MATERIAL	From	To	SWL
Size of perforations 3/8 in. by 8 in.	Gravel	0	17	52
352 perforations from 50 ft. to 260 ft.	Gravel some clay	_ 	47	
	Brown clay very little gr		63	
perforations from ft. to ft.	Gravel little clay	_	66	55
periorations from	Cemented gravel		<u>8</u> 3	
(7) SCREENS: Well screen installed? ☐ Yes I No	Brown clay little rock	_	115	
Manufacturer's Name	Gravel and some clay	115	125	
Type Model No	Brown clay	125	130	
Diam. Slot size Set from ft. to ft.	Cemented gravel	130	187	
Diam. Slot size Set from ft. to ft.	Brown clay		190	
(8) WELL TESTS: Drawdown is amount water level is	Gravel cemented		197	
lowered below static level	Brown sticky clay		200	
Was a pump test made? Yes No If yes, by whom?	Brown clay		260	E 6
Yield: 150 gal./min. with 169 ft. drawdown after 3 hrs.	Gravel some clay	260		56
" " "				
" " " "				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
'emperature of water 53 Depth artesian flow encountered ft.	Work started 1-12 1982 Complete	a 3-1		182
(9) CONSTRUCTION:	Date well drilling machine moved off of well	3-1		1982
Well seal-Material used Cement grout	Drilling Machine Operator's Certification:			
Well sealed from land surface to 20 ft.	This well was constructed under my			
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief.	above a	re true	to m
Diameter of well bore below seal10 in.	1 1 1 1 1 1 1 1 1 1	Date 3-	-5	1982
Number of sacks of cement used in well seal	(Drilling Machine Operator)	E 1 E		,
How was cement grout placed?poured	Drilling Machine Operator's License No.	545	······	
	Water Well Contractor's Certification:			
	This well was drilled under my jurisdi	ction and	d this r	eport i
Was a drive shoe used? ■ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and bel	ief.		_
Did any strata contain unusable water? Yes No	Name G.L."Lee" Parr well D (Person, firm or corporation)		g	
Type of water? depth of strata	DA 7 D 71	n-Free	_	
Method of sealing strata off		44 .		
Was well gravel packed? Yes No Size of gravel:	[Signed] (Water Well Contr	actor)	••••••	•••••••
Gravel placed from ft. to ft.	Contractor's License No7.30 Date	3-5		, 19.8