

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date of well completion.

UMATILLA
4878

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

State Well No. 6N/35E-33db

State Permit No. G-9344
umatilla

(1) OWNER:

Name MURTIE JEAN TUCKER
Address 406 N Broadway
Miller-Freewater, Ore 97862

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
C Jetted
L Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

(5) CASING INSTALLED:

Threaded Welded
10" Diam. from +1 ft. to 19 ft. Gage 250
8" Diam. from +2 ft. to 7.5 ft. Gage 250

(6) PERFORATIONS:

Perforated? Yes No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name Model No.
Type Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

as a pump test made? Yes No If yes, by whom? Air tested
Yield: 300 gal./min. with 72 ft. drawdown after 1 hrs.
" " " " " "
" " " " " "
Trailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water 56 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 14 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 10 sacks
How was cement grout placed? PUMPED

Was a drive shoe used? Yes No Plugs Size: location ft.

Did any strata contain unusable water? Yes No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Driller's well number
NW 1/4 SE 1/4 Section 33 T. 6N R. 35E W.M.
Bearing and distance from section or subdivision corner:

(11) WATER LEVEL: Completed well.

Depth at which water was first found 75 ft.
Static level 48 ft. below land surface. Date 3-28-80
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 140 ft. Depth of completed well 140 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Soil	0	2	
gravel	2	10	
Clay + Black loam	10	75	
Black & Red Basalt Breccia	75	140	H ₂ O

Work started 3-27 1980 Completed 3-28-80 1980

Date well drilling machine moved off of well 3-28 1980

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Judd Hon Date 3-28, 1980
(Drilling Machine Operator)

Drilling Machine Operator's License No. 1345

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Judd Hon Well Drilling
(Person, firm or corporation) (Type or print)

Address RT Box 14 Pilot Rock, Ore 97862

[Signed] Judd Ho
(Water Well Contractor)

Contractor's License No. 739 Date 3-28, 1980