of this report are to be DEGEIVE TATE OF OREGON tate Well No. . STATE ENGINEER, SALEM, OREGON SAP 9 1970 Glease type or print) within 30 days from the date
of well completion STATE ENGINEER State Permit No. .... (Do not write above this line) SALLM ORLSON (10) LOCATION OF WELL: 97 WSB (1) OWNER: County Umatilla Driller's well number Vernon C. Lane Name Rt 2 Box 31-A 30 R. Address Echo. Oregon Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): Abandon [] Deepening [ Reconditioning [ New Well F If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found ft. below land surface. Date 8-10-Twenty Rotary Driven | Static level Domestic 1 Industrial | Municipal | Cable Jetted | Irrigation | Test Well | Other lbs. per square inch. Date Bored | Artesian pressure Dug CASING INSTALLED: Threaded | Welded | (12) WELL LOG: Diameter of well below casing . 10 Diam. from 0 ft. to 58 ft. Gage 0.250 Depth drilled ft. Depth of completed well " Diam. from ...... ft. to ...... ft. Gage Formation: Describe color, texture, grain size and structure of materials; " Diam. from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Gage .... and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? Tyes Vo. MATERIAL pe of perforator used Clay, White soft Clay, Brown, Soft 15 in. by Size of perforations 42 \_\_\_ perforations from \_\_\_\_\_ ft. to \_\_\_ Basalt, Gray, Soft 42 48 ... perforations from ..... ft. to ..... 48 52 Gravel, Medium \_\_\_ perforations from \_\_\_\_\_ft. to \_ 52 70 Basalt, Gray, Hard (7) SCREENS: 20 80 Well screen installed? ☐ Yes 🛣 No Basalt, Grav. Porous 70 Manufacturer's Name ..... 70 to 80 Feet - Water Bearing Diam. Slot size Set from ft. to ft. Diam. Slot size Set from Drawdown is amount water level is lowered below static level (8) WELL TESTS: Was a pump test made? 

Yes No If yes, by whom? ft. drawdown after hrs. gal./min. with gal./min. with 20 ft. drawdown after 1 Artesian flow hmperature of water 55 Depth artesian flow encountered \_\_\_\_\_ ft. 8-6-1970 Completed Aug. 10th 1970 Date well drilling machine moved off of weaug. 10th CONSTRUCTION: **Drilling Machine Operator's Certification:** Cement Well seal-Material used .... This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. Well sealed from land surface to Fifty-eight Diameter of well bore to bottom of seal thirteen in. 11K Date Aug. 10 19 70 [Signed] Cance & Diameter of well bore below seal 8 3/4 in. Number of sacks of cement used in well seal Seventeen Drilling Machine Operator's License No. ..... Number of sacks of bentonite used in well seal ..... Brand name of bentonite Water Well Contractor's Certification: Number of pounds of bentonite per 100 gallons This well was drilled under my jurisdiction and this report is lbs./100 gals. true to the best of my knowledge and belief. Name PROJECT: Corporation (Person, firm or corporation) Did any strata contain unusable water? 🗌 Yes 💾 No 4 North Second Street, Walla Walla, depth of strata Type of water? Method of sealing strata off Was well gravel packed? ☐ Yes ☐ No Size of gravel: ... Mate Sept/8th/ Gravel placed from ...... ft. to .....

WATER WELL REPORT

NOTICE TO WATER WELL CONTRACTOR The original and first copy