NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)



State Well No. Lon 356-346c

(1) OWNER: / / ·	(10) LOCATION OF WELL:	
Name Jim WALLSON	County UMa+(A Driller's well number	
Address Pt 2 Box 226	01.1 All1/ 01/ 11 05 -	
Salvauist Rd Milton-Frequete Or		W.M.
(2) TYPE OF WORK (check): 9R	Bearing and distance from section or subdivision corner	
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
if abandonment, describe material and procedure in Item 12.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.	
The state of the s	Depth at which water was first found /90	ft.
Domestic Industrial Municipal	Static level 58 ft. below land surface. Date	
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded \(\Pi \) Welded \(\Pi \)		
(3) CASING INSTALLED: Threaded Welded Welded Welded Threaded Welded Welded Threaded Welded We	(12) WELL LOG: Diameter of well below casing	8
8 " Diam. from +2 ft. to 98 ft. Gage 250	Depth drilled 360 ft. Depth of completed well 36	ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of a	materials;
Total Itoli management to to sometime to Gage management	and show thickness and nature of each stratum and aquifer powith at least one entry for each change of formation. Report each	enetrated,
(6) PERFORATIONS: Perforated? Yes 4.70.	position of Static Water Level and indicate principal water-bearing	ng strata.
Type of perforator used	MATERIAL From To	SWL
Size of perforations in. by in.	gravel 0 8	
perforations fromft. toft.	CVAn & Bosalh . 8 190	
perforations fromft. toft.	READ Bosalr & Vellos clay 190 270	1120
perforations fromft. toft.	Brown Clay + BASALT / 270 325	1730
	RED Bas Alt of ROUN Clay 325 360	H20
(7) SCREENS: Well screen installed? Yes		, ,
Manufacturer's Name		
TypeModel No.		
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.		
Jam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	man had been a fill the first the fill	
a pump test made? Yes No If yes, by whom?	WATER RESOURCES DEPT	
rield: /50 gal./min. with 335ft. drawdown after / hrs.	S. LEM. OREGON	
II	IS LESI. OREGON &	
" " "	***	
er test gal./min. with ft. drawdown after hrs.	.22	
artesian flow g.p.m.	5-	
Temperature of water 65 Depth artesian flow encountered ft.	Work started 2-28 1980 Completed 3-1	1980
(a) CONCERNICATION -	Date well drilling machine moved off of well 3-/-	19 80
(9) CONSTRUCTION PORTLAND CEMENT		
	Drilling Machine Operator's Certification: This well was constructed under my direct super	rrial on
41/	Materials used and information reported above are true	
Diameter of well bore to bottom of sealin.	best knowledge and belief. [Signed] ADD HOW Date 4-8	00
Number of sacks of cement used in well seal sacks	[Signed] Date (Drilling Machine Operator)	, 19 80
Now was cement grout placed? Dum 160	Drilling Machine Operator's License No. 1345	
The content growt placed:		
	Water Well Contractor's Certification:	
	This well was drilled wider my jurisdiction and this r	eport is
Vas a drive shoe used? 14 Yes No Plugs Size: location ft.	true to the best of my/knowledge and belief.	lna
old any strata contain unusable water? Yes	Name Person, firm or corporation 7	ממו
'ype of water? depth of strata	Address Kt BOXLY, PICOT LOCK	Jer .
Method of sealing strata off	Jald L	97/68
Vas well gravel packed? Yes Zino Size of gravel:	[Signed] (Water Well Contractor)	*
ravel placed from	Contractor's License No. 739 Date 4-8	10Pm