

The original and first copy of this report are to be filed with the

RECEIVED

WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310

within 30 days from the date of well completion

SEP 7 1978

(Please type or print)

WATER RESOURCES DEPT. SALEM, OREGON

(Do not write above this line)

NO UMAT 4937

State Well No. 6N/35E-34ka

State Permit No.

(1) OWNER:

Name Dave DOWRIE
Address P.O. BOX 552 CORVALLIS OR

(2) TYPE OF WORK (check):

New Well [] Deepening [x] Reconditioning [] Abandon []
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Driven []
Cable [x] Jetted []
Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [] Industrial [] Municipal []
Irrigation [x] Test Well [] Other []

(5) CASING INSTALLED:

8" Diam. from 1 ft. to 56 ft. Gage 0.250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? [] Yes [x] No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level
Was a pump test made? [x] Yes [] No If yes, by whom? SUMC
Yield: 150 gal./min. with 36 ft. drawdown after 1 hrs.
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 59 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Bentonite
sealed from land surface to 36 ft.
Diameter of well bore to bottom of seal 20 1/2 in.
Diameter of well bore below seal in.
Number of sacks of Bentonite used in well seal 4 sacks
How was cement grout placed?
Was a drive shoe used? [x] Yes [] No Plugs Size: location ft.
Did any strata contain unusable water? [] Yes [x] No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? [] Yes [x] No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
NE 1/4 SW 1/4 Section 34 T. 6N R. 35E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 87 ft.
Static level 32 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled ft. Depth of completed well ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with columns: MATERIAL, From, To, SWL. Rows include Hand Dug, Boulders + Gravel, Cement Gravel.

Work started 8-5-1977 Completed 8-7-77 19
Date well drilling machine moved off of well 8-7-77 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] [Signature] Date 9-2-1977
Drilling Machine Operator's License No. 821

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name C.W. SUMMERS Well Drilling
Address Rt 43 Box 143-1-1777 OR
[Signed] [Signature]
Contractor's License No. 575 Date 9-2-1977