RECEIVED

STATE OF OREGON

JUL8 1985

WATER WELL REPORT
(as required by ORS 537.765) WATER RESOURCES DEPT

SALEM: OBEGON
(CO. LOCAT

(for official use only)

(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name FRONKILLE	County Umatila National of of
Address PHBBDY 154C	
City Milton FREGULATOR, OR State 97862	(Township is North or South) (Range is East or West)
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address) Sa TWR
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal D	Depth at which water was first found
Thermal: Rotary Mud □ Dug □ Irrigation □ Withdrawal □ Reinjection □	Static level 36 ft. below land surface. Date 5-30-35
Other:	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel Plastic	Depth drilled 102 Diameter of well below casing
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness
	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal
"Diam. from	water-bearing strata.
LINER INSTALLED: Steel Plastic Plastic	MATERIAL From To SWL
Threaded	Soil Grand & Road Jan 8
"Diam. from	Jell Glore Bee
(6) PERFORATIONS: Perforated? Yes No	
Size of perforations in. by in.	Clay apavel + Bouldes 22 55
perforations from ft. to ft.	Cement GRAVEL 53 102 36
perforations from ft. to ft.	
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes Pro	
Manufacturer's Name	
Type	- And
DiamSlot SizeSet fromft. toft.	
Diam. Slot Size Set from ft. to ft.	
Decidence	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
" " "	
Air test 500 gal./min. with drill stem at 85 ft. / hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water 58 Depth artesian flow encounteredft.	
9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \)	Date work started 5-21-83 /completed 5-30-85
Vell seal—Material used Cement	Date well drilling machine moved off of well 5-30 1985
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and
Diameter of well bore below seal	information reported above are true to my best knowledge and belief.
amount of sealing material sacks pounds	[Signed], 19,
Now was cement grout placed?	
	(bonded) Water Well Constructor Certification: Bond Issued by:
and the second s	Bond Issued by; (Surety Company Name)
Vas pump installed? Depth	On behalf of
Vas a drive shoe used? Yes \(\square\) No Plugs Size: location ft.	(type or print name of Water Well Constructor)
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction and this report is true to the
'ype of Water? depth of strata	best of my knowledge and belief:
fethod of sealing strata off	(Signed) Chairman (Water Well Constructor)
Vas well gravel packed? Yes No Size of gravel:	
ravel placed from ft. to ft.	(Dated) 4 - 6 - 5 5