

NC

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

RECEIVED MAY 27 1968

RECEIVED STATE ENGINEER SALEM, OREGON MAY 13 1968

STATE OF OREGON STATE ENGINEER SALEM, OREGON G-4450

State Well No. 6N/36-30M

State Permit No. UMAT 5208

(1) OWNER:

Name Bill Morris Address RT# 2 Milton Freewater, Ore

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Driven [] Cable [x] Jetted [] Dug [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 69 ft. Gage 1250

PERFORATIONS:

Perforated? [] Yes [x] No

Type of perforator used

Size of perforations in. by in. perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 24 ft. below land surface Date May 6 68

Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [x] No If yes, by whom

50 gal./min. with 60 ft. drawdown after 2 hrs.

Bailer test 50 gal./min. with 60 ft. drawdown after 2 hrs.

Artesian flow g.p.m. Date

Temperature of water 50 Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used Bentonite

Depth of seal 21 ft.

Diameter of well bore to bottom of seal 10 in.

Were any loose strata cemented off? [] Yes [x] No Depth

Was a drive shoe used? [x] Yes [] No

Did any strata contain unusable water? [] Yes [x] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [x] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Umatilla Driller's well number 1/4 1/4 Section T. R. W.M.

Bearing and distance from section or subdivision corner Well located 30 ft. N - 30 ft. E of property SW corner

(12) WELL LOG:

Diameter of well below casing 6

Depth drilled 135 ft. Depth of completed well 124 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include Top Soil + clay, Conglomerate (Brown), Med. Fine Gravel (Some water + Sand), Brown Cement Gravel, Med. Gravel some water, Black Sand Med. Fine., Fine Black Sand, Brown Cement Gravel, Yellow Brown clay.

Work started April 25 1968 Completed May 6 1968

Date well drilling machine moved off of well May 8 1968

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Lowell W. Marlatt Date May 6, 1968 (Drilling Machine Operator)

Drilling Machine Operator's License No. 11

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Lowell W. Marlatt (Person, firm or corporation) (Type or print)

Address RT# 2 Box 111A Milton Freewater, Ore

[Signed] Lowell W. Marlatt (Water Well Contractor)

Contractor's License No. 265 Date May 6, 1968

Bill Morris
Rt. #3
Milton-Freewater, Ore.

6N/36-30M
Umatilla
RECEIVED
MAY 13 1968
STATE ENGINEER G-4450
SALEM, OREGON

Beginning at the Southeast corner of the North half of the Northwest Quarter of the Southwest Quarter of Section 30, Township 6 North, Range 36, E.W.M.; thence West along the South line thereof a distance of 410 feet; thence North at right angles a distance of 310 feet; thence East and parallel to the South line of the North Half of the Northwest Quarter the East line of the said North half of the Northwest Quarter of the Southwest Quarter; thence South along said East line a distance of 310 feet to the point of beginning.

All being East of the Willamette Meridian, in the County of Umatilla and State of Oregon.

Excepting therefrom any and all water rights of way and roads.

