The original and first copy of this report are to be filed with the WATER RESOURCES DEPARTMENT, DEC 0.5 198 STATE OF OREGON SALEM, OREGON 97310 within 30 days from the date ATER RESOURCES DEPT. above this line) State Permit No. SALEM, OREGON (1) OWNER: (10) LOCATION OF WELL: J. Frank Schmidt & Son Co. Name County Umatilla Driller's well number 9500 SE 327th Av Boring, Or 97009 SE 14 Section 31 T. 6N R. 36E Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well □ Deepening [7] Reconditioning [Customer Well #1 Milton Nursery If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found unknown Driven | Domestic | Industrial | Municipal | Static level Jetted [] ft. below land surface. Date Bored D REMOVED Irrigation

Test Well

Other Artesian pressure lbs. per square inch. Date (5) CASING INSTANTATION (12) WELL LOG: Diameter of well below casing ft. to Depth drilled ft. Depth of completed well " Diam, from Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in (6) PERFORATIONS: position of Static Water Level and indicate principal water-bearing strata. Perforated? A Yes No. Mills Knife Type of perforator used Size of perforations in. by See attached letter to DWR of 10/21/80 and return letter to Schneider Equipment perforations from Inc. of 10/22/80 attached to this log/ .. perforations from ... __ perforations from Abandonment consisted of: (7) SCREENS: Well screen installed? Yes 1. Perforating 10" cading with 4 holes Manufacturer's Name every 25' from 5' to 125'
2. Pumping in 405 sacks neat cement Diam. Slot size Set from ft. to from 333' to 5' Diam. Slot size Set from ft. to ____ ft. Cutting off 12" and 10" casings 5' below ground Drawdown is amount water level is lowered below static level (8) WELL TESTS: 4. Backfilling top 5' with native s a pump test made? 🗌 Yes 🌋 No If yes, by whom? Yield: gal./min. with ft. drawdown after iler test gal./min. with ft. drawdown after Artesian flow g.p.m. Temperature of water Depth artesian flow encountered 11-7 8Q_{completed} 19 80 11-13 Work started 19___ (9) CONSTRUCTION: Date well drilling machine moved off of well 19 80 Well seal-Material used-5 ft neat cement Drilling Machine Operator's Certification: Well sealed from land surface to 333 This well was constructed under my direct supervision. Materials used and information reported above are true to my Diameter of well bore to bottom of seal see attachedn sketch best knowledge and belief. Diameter of well bore below seal [Signed] Amald A Lars Date 12-2 19 80 Number of sacks of cement used in well seal (Drilling Machine Operator) Drilling Machine Operator's License No. 1085 How was cement grout placed? pumped down grout pipe from bottom of open hole to within 5' of surface Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is et. n. moraret m. Maranana, and Santa 12 true to the best of my knowledge and belief. Was a drive shoe used? His now Plugs Size: location ft. Name Schneider Equipment, Inc.

(Type or print)

(USE ADDITIONAL SHEETS IF NECESSARY)

Address

649

Did any strata contain unusable water? 🔲 Yes 🔼 No

Was well gravel packed? [] Yes 🕱 No -- Size of gravel:

Type of water?

Method of sealing strata off