NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

APR

Do	not	write	above	this line)	•	

State Permi

	Appeter 1985	9	Lal	170		
	State	Well No.		1295	5 1d	,
33	1977		/			۰
	Stata	Danmit N	TA /			

	, ye., pr. talaya j	_	
(1) OWNER:	(10) LOCATION OF WELL:		
Name Q. E. Staley Manufacturing Co.	County Umalilla Driller's well no	ımhar	
Address Necature Illinois	N-E 1/4 SE 1/4 Section 31 T. 491		Y17.36
, , , , , , , , , , , , , , , , , , , ,	Bearing and distance from section or subdivisi		W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner	
New Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w		
(3) TYPE OF WELL: (4) PROPOSED USE (check):		en.	
Rotary M Driven D	Depth at which water was first found 21		ft.
Cable	Static level /5 ft. below land s Artesian pressure lbs. per squar		.15-77
CACING INCHALLED.	Artesian pressure lbs. per squar		
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well b	pelow casing 6	K
6 "Diam from 6 ft to 6 ff ft Gage 250	Depth drilled /35 ft. Depth of comple	eted well /3	5 ft.
" Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a	and structure of n	naterials;
Diam. from	and show thickness and nature of each stratus with at least one entry for each change of format	m and aquifer pe	netrated
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearin	nange in Ig strata.
Type of perforator used	MATERIAL	From To	SWL
Size of perforations in. by in.	Tobasie		
perforations fromft. toft.	Sand T gravel	10 21	
perforations fromft. toft.	Grand	21 37	
perforations fromft. toft.	Grave & brown clay Tone	37 48	
	Claustone, White	48 56	
(7) SCREENS: Well screen installed? Yes St No	Rock black	56 125	W.B.
Manufacturer's Name	Rock black & red	125 135	WB
Type Model No.			
Diam. Slot size Set from ft. to ft.	-		
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is			
lowered below static level			
Was a pump test made? Yes No If yes, by whom?			
d: gal./min. with ft. drawdown after hrs.			
" " "	.86 /		-
Cur 80 " 65 ft. " 1 "	- 175 14 2 1 4 1 2 1 4 1 4 1 4 1 4 1 4 1 4 1		
Bailer test 60 gal./min. with 45 ft. drawdown after / hrs.			
Artesian flow g.p.m.			
perature of water Depth artesian flow encountered ft.	Work started 4-/4 19 77 Complete	d 4-15	1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4-15	19 77
Well seal-Material used Cement	Drilling Machine Operator's Certification:		_
Well sealed from land surface to 64	This well was constructed under my	direct superv	vision.
Diameter of well bore to bottom of sealin.	Materials used and information reported best knowledge and belief.	above are true	to my
Diameter of well bore below seal		Date 4-18	1011
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)		, 118.A.A.
How was cement grout placed?	Drilling Machine Operator's License No.	1011	The sense agency
,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人,我们就是一个人	Water Well Contractor's Certification:		r _{an} 21 — 14 2 5
	This well was drilled under my jurisdie	ction and this re	eport is
Was a drive shoe used? ▼ Yes □ No Plugs Size: location ft.	true to the best of my knowledge and beli	ef.	
Did any strata contain unusable water? Yes No	Name TROY GRIFFIN (Person, firm or corporation)	/Pd	4
Type of water? depth of strata	Address 900 HERM 13 TOWAVE	(Type or print	•
Method of sealing strata off	T 11 100		XII
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	[Signed]	U J	RE-V-V
Gravel placed from ft. toft.		4-18	10 77
11. 10	Contractor's License No. Date		, 19 <i>!</i> (