MEGELLEN

STATE OF OREGON WATER WELL REPORT
(as required by ORS 537.765) JUL 18 1988

WATER RESOURCES DEPT.

PAGE

(for official use only)

OWNER:	(10) LOCATION OF WELL by legal	
Rame Barkeley F. Davis	County umatile SE 1/4 c	of Sectionof
Address PO Roy 18	Township 3 N Range	34 E, wm.
City Adama Cos State	(Township is North or South)	Range is East or West)
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision MAILING ADDRESS OF WELL (or nearest address)	
	MAILING ADDRESS OF WELL (or nearest address)	
New Well		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL of COMPLET	ED WELL.
(3) TYPE OF WELL: (4) PROPOSED USE (check):		ft.
Rotary Air Driven Domestic Industrial Municipal Thermal:	Depth at which water was first found Static level 75 ft. below	land surface. Date 6-/5-8
Rotary Mud Dug Irrigation Withdrawal Reinjection	124	square inch. Date
□ Bored □ Other: Piezometric □ Grounding □ Test □		. ~ 1
(5) CASING INSTALLED: Steel Plastic Threaded Welded		f completed well 1000 ft.
Threaded Welded Threaded Welded 37.5	Formation: Describe color, texture, grain size and structure and nature of each stratum and aquifer penetrated, with at l	of materials; and show thickness east one entry for each change of
Diam. from ft. to ft. Gauge	formation. Report each change in position of Static Wat	
	water-bearing strata.	
LINER INSTALLED: Steel Plastic D	MATERIAL	From To SWL
	SOIL	8 0
	BASALT BLACK	8 17
(6) PERFORATIONS: Perforated? ☐ Yes ☐ No Size of perforations in. by	ReD	17 30
Other of periodicion	GRAY	30 77
perforations from	BLACK	77 92
perforations from	- GRAY_	92 95
perforations from ft. to ft.	ReD	95 113
SCREENS: Well screen installed? Yes	GRAY .	113 175
anufacturer's Name	BLACK	175 200
Type	GRAY	210 271
Diam. Slot Size Set from ft. to ft.	BLACH	271 285
Diam. Slot Size Set from ft, to ft.	GRAY	285 295
Drawdown is amount water level is lowered	DEALIFEBLACH	295 320
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	L. C. RAY	320 340
a pump test made? Yes Yes You if yes, by whom?	BLACH	340 360
Meld: 700 gal./min. with 10 ft. drawdown after 10 hrs.	SEP 271989 GRAÝ	360 385
, , , , , , , , , , , , , , , , , , ,	BLACK	385 400
Air test gal./min. with drill stem at ft. hrs.	WATER RESOURCES DELACH	400 412
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON BROWN	412 420
sian flow g.p.m.	BLACH	A20 425
Temperature of water 70° C Depth artesian flow encountered ft.	Continued	: :
(A) CONCERNICATION.	Date work started 5-26-88 /complet	ed 6-15-88
(9) CONSTRUCTION: Special standards: Yes \(\text{No } \)	Date well drilling machine moved off of well	19
	(unbonded) Water Well Constructor Certific	ation (if applicable):
Well sealed from land surface to	This well was constructed under my direct sur	pervision. Materials used and
Diameter of well bore to bottom of seal in.	information reported above are true to my best kn	owledge and belief.
Diameter of well bore below seal	[Signed] Jarry Burl	Date 6-15 , 1988
Amount of sealing material sacks pounds How was cement grout placed?	[Digitor]	
How was cement grout placed?	(bonded) Water Well Constructor Certificati	.on:
	Bond Issued by:(Su	rety Company Name)
Was pump installed? Type HP Depth	On behalf of	
	(type or print name of W	ater Well Constructor)
Was a drive shoe used? Yes No Plugs Size: location ft.	This well was drilled under my jurisdiction and this report is true to the	
e of Water? depth of strata	best of my knowledge and belief:	***
	Janes Bus	
Method of sealing strata off	(Signed) (Water Well Construction	tor)
Was well gravel packed? Yes No Size of gravel:	(Dated) 6-15-88	·····
Gravel placed fromft. toft.	WAMED DESCRIPCING DEDARCH	OD#40000 000
NOTICE TO WATER WELL CONSTRUCTOR	WATER RESOURCES DEPARTMENT.	SP*46866-690

STATE OF OREGON

RECEIVED AGE 2

WATER WELL REPORT (as required by ORS 537.765)

JUL 18 1968 PLEASE TYPE or PRINT IN INK

3n/3	4E/5d
7	7

(for official use only)

(1) OWNER: WATER RESOURCES BEAT (1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL by legal description:	
Name BerkelEY FAUIS	County	
Address P O Box 18	The state of the s	
City ADAMS OR State	(Township is North or South) (Range is East or West)	
(2) TYPE OF WORK (check):	Tax Lot Lot Subdivision MAILING ADDRESS OF WELL (or nearest address)	
New Well □ Deepening □ Reconditioning □ Abandon □	The state of the s	
If abandonment, describe material and procedure in Item 12.		
(11) MIAMED I DIVEL - COMET BUILD WELL.		
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found ft.	
Thermal:	Static level ft. below land surface. Date	
Rotary Mud Dug Irrigation Withdrawal Reinjection Dther:	Artesian pressure lbs. per square inch. Date	
Bored Diezometric Grounding Test		
(5) CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing	
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness	
"Diam. fromft. toft. Gauge	and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal	
"Diam. fromft. toft. Gauge	water-bearing strata.	
LINER INSTALLED: Steel Plastic	MATERIAL From To SWL	
Threaded Welded	BASALT GRAY 425 458	
	BLACK 458 480	
(6) PERFORATIONS: Perforated? Yes No	GRAY 480 550	
Size of perforations in. by in.	BLACK 550 560	
perforations from ft. to ft.	BLACH 560 600	
perforations from ft. to ft.	GRAY 600 617	
perforations from ft. to ft.	BLACH 617 630	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	GRAY 630 800	
Manufacturer's Name	84ACH 800 815	
TypeModel No	GRAY 815 861	
Diam. Slot Size Set from ft. to ft.	BLACH 861 872	
Diam. Slot Size Set from ft. to St. ft.	BLACH 872 874	
Drawdown is amount water level is lowered	BLACK 874 909	
(8) WELL TESTS: below static level	GRAY 909 948	
a pump test made? Yes No If yes, by whom?	DEPEND RED 948 950	
Yield: gal./min. with ft. drawdown after hrs.	BLACK 950 965	
. и и и	SEP 27 1989 BROWN 972 980	
Air test gal./min. with drill stem at ft. hrs.	SEP 2 1 1903 BROWN 972 980	
Bailer test gal./min. with ft. drawdown after hrs.	GRAY 980 1000	
sian flow g.p.m. WAT	SALEM, OREGON	
Temperature of water Depth artesian flow encountered ft.	SALEM, ONLOOK	
(9) CONSTRUCTION: Special standards: Yes \(\square\) No \(\square\)	Date work started/completed	
(9) CONSTRUCTION: Special standards: Yes \(\subseteq \) No \(\subseteq \) Well seal—Material used	Date well drilling machine moved off of well 19	
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):	
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used and	
Diameter of well bore below seal in.	information reported above are true to my best knowledge and belief.	
Amount of sealing materialsacks _ pounds _	[Signed]	
How was cement grout placed?		
110W Was cement grout placeur.	(bonded) Water Well Constructor Certification:	
- 4	Bond Issued by: (Surety Company Name)	
Was pump installed? Type HP Depth ft.	On behalf of	
Was a drive shoe used?		
Did any strata contain unusable water? 🔲 Yes 🔲 No	This well was drilled under my jurisdiction and this report is true to the	
Type of Water? depth of strata	best of my knowledge and belief:	
Method of sealing strata off	(Signed)(Water Well Constructor)	
Was well gravel packed? Yes No Size of gravel:	(Dated)	
Gravel placed from ft. to ft.		