STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

WELL LABEL # L	82868
START CARD #	181334

(1) LAND OWNER Owner Well I.D. #13	(9) LOCATION OF WELL (legal description)	
First Name Craig Last Name Coleman	County UMATILLA Twp 4,00 N N/S Range 27,00 E E/WWM	
Company Girth Dog, LLC.	Sec 27 SW 1/4 of the NW 1/4 Tax Lot 1803	
Address 33896 E. Walls Rd	Tax Map Number Lot	
City Hermiston State OR Zip 97838	Lat *0 ' "or DMS or DD	
	Long O O O DD	
(2) TYPE OF WORK New Well Deepening Conversion Alteration (repair/recondition) Abandonment	Street address of well • Nearest address	
(3) DRILL METHOD	28286 Stafford Hansel Rd, Hermiston, OR 97838	
Rotary Air Rotary Mud Cable Auger Cable Mud Reverse Rotary Other	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)	
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening Completed Well 03-09-2006 88.	
Industrial/ Commericial Livestock Dewatering	Flowing Artesian?	
Thermal Injection Other	WATER BEARING ZONES Depth water was first 90.	
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy	With Derivation 2011es	
Depth of Completed Well 119. ft.	03-06-2006 109. 114. 150. 88.	
BORE HOLE SEAL sacks/		
Dia From To Material From To Amt lbs		
28. 0 19. Cement 0 3. 4. S		
24. 19. 119. Granular Bentoniti 3. 19. 30. S		
(11) WELL LOG Ground Elevation		
How was seal placed: Method A B XC D E	Material From To	
Other	Top soil / sandy 0 4.	
Backfill placed from 114.5 ft. to 119. ft. Material clean gravel	Gravel (1.5") - tight	
Filter pack from ft. to ft. Material Size	Gravels (tight) w/ clay	
Explosives used: Type Amount	Gravel (1-2") 109. 114.	
(6) CASING/LINER	Brown clay 114. 119.	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wid Thrd		
② 24. X 1. 19375③ X 		
24. 19. 105. 375 X		
	RECEIVED	
	TILOLIVLO	
Shoe Inside Outside Other Location of shoe(s)	May 0.9.2000	
Temp casing Yes Dia From To	MAY 0.3 2006	
(7) PERFORATIONS/SCREENS	WATER RESCUENCES DERT	
Perforations Method Screens Type wire wrap Material 304 SS	WATER RESOURCES DEPT SALEM, OREGON	
Screens Type Wile Wrap Waterial 304-35		
Scree /Liner Dia From To width lengt slots pipe Date started 02-23-2006 Completed 03-10-2006		
Screen Liner 24. 103.6 114.5 .125 0	(unbonded) Water Well Constructor Certification	
Screen Liner 24. 103.6 114.5 .125 0	I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well	
	construction standards. Materials used and information reported above are true	
	to the best of my knowledge and belief.	
(8) WELL TESTS: Minimum testing time is 1 hour	License Number 1672 Date 5-1-06	
Pump Bailer Air Flowing Artesian	Password : (if filing electronically) Signed	
Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) 150. 31. 119 1.	(bonded) Water Well Constructor Oertification	
	I accept responsibility for the construction, deepening, alteration, or	
	abandonment work performed on this well during the construction dates	
Temperature 57 °F Lab analysis Yes By	reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best	
Water quality concerns? Yes (describe below)	of my knowledge and belief.	
From To Description Amount Units	License Number 1523 Date 5-1-06	
	Password: (if filing ejectron cally)	
	Signed What S	
	Contact Info	