UMAT 56674

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

09-13-2010

WELL LABEL # L 46663 START CARD # 1011322

Page 1 of 2

(1) LAND OWNER Owner Well I.D.	(9) LOCATION OF WELL (legal description)
First Name JOHN Last Name OWEN	County Umatilla Twp 100 X S N/S Range 31 00 E E/W WM
Company	Sec _7 NE 1/4 of the NW 1/4 Tax Lot 1000
Address PO BOX E	Tax Map Number Lot
City PILOT ROCK State OR Zip 97868-0080	Lat o o or DMS or DD
(2) TYPE OF WORK New Well Deepening Conversion	Long o j or DMS or DD
Alteration (repair/recondition)	€ Street address of well
(3) DRILL METHOD	69167 OWEN LANE PILOT ROCK. OR
Rotary Air Rotary Mud Cable Auger Cable Mud	(10) CT A TIC WA TER A FUEL
Reverse Rotary Other POURED BENTONITE	(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft)
(4) PROPOSED USE Domestic Irrigation Community	Existing Well / Predeepening
Industrial/Commercial Livestock Dewatering	Completed Well
Thermal Injection Other	Flowing Artesian? Dry Hole?
(5) BORE HOLE CONSTRUCTION Special Standard Attach copy	WATER BEARING ZONES Depth water was first found SWL Date From To Est Flow SWL(nsi) + SWL(ft)
Depth of Completed Well ft.	SWL Date From To Est Flow SWL(psi) + SWL(ft)
BORE HOLE SEAL sacks	
Dia From To Material From To Amt Ibs	
	(11) WELL LOG Ground Elevation
How was seal placed: Method A B C D E	Material From To
Other	
Backfill placed from ft. to ft. Material Filter pack from ft. to ft. Material Size	
Explosives used:Yes Type Amount	
(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	
Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd	
	DECENTS -
	The Charles and the Charles an
Shoe Inside Outside Other Location of shoe(s)	OCT 0 1 2010
Temp casing Yes Dia From To	001 01 2010
(7) PERFORATIONS/SCREENS	WATER RESOURCES DEPT
Perforations Method	SALEM, OREGON
Screens Type Material	SALEM, OHLOOM
Perf/S Casing/ Screen Scrn/slot Slot # of Tele/ creen Liner Dia From To width length slots pipe size	Date Started 09-09-2010 Completed 09-09-2010
From 10 Widdi length 3103 pipe 5125	(unbonded) Water Well Constructor Certification
	I certify that the work I performed on the construction, deepening, alteration, or
	abandonment of this well is in compliance with Oregon water supply well
	construction standards. Materials used and information reported above are true to the best of my knowledge and belief.
(8) WELL TESTS: Minimum testing time is 1 hour	
`	License Number 1735 Date 09-13-2010 Electronically Filed
Pump Bailer Air Flowing Artesian Yield gal/min Drawdown Drill stem/Pump depth Duration (hr)	Signed CHAD COURTNEY (E-filed)
Tiolo gairtinii Diandonii Dini seriat unip deput Duration (iii)	(bonded) Water Well Constructor Certification
	I accept responsibility for the construction, deepening, alteration, or abandonment
	work performed on this well during the construction dates reported above. All work
Temperature 60 °F Lab analysis Yes By	performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.
Water quality concerns? Yes (describe below) From To Description Amount Units	1
	License Number 1881 Date 09-13-2010 Electronically Filed
	Signed GARRY L ZOLLMAN (E-filed)
	Contact Info (optional)

UMAT 56674

WATER SUPPLY WELL REPORT continuation page

UMAT 56674

WELL I.D. # L 46663 Page 2 of 2

09-13-2010

START CARD # 1011322

(5) BORE HOLE CO		(10) STATIC WATER LEVEL
BORE HOLE	SEAL sack	
Dia From To	Material From To Amt Ibs	- J
		SWL Date From To Est Flow SWL(psi) + SWL(ft)
		<u> </u>
		-
TIL TED DACK		·
FILTER PACK From To N	Material Size	
		- (11) WELL LOC
(6) CASING/LINER	:	- (11) WELL LOG
(U) CASING/LINER		Material From To
Casing Liner Dia	+ From To Gauge Stl Piste Wid Thrd	
\circ		
$Q Q \square$		
Q		
\aleph		
 		
88		
88		
8 8		
		_
(7) PERFORATION	S/SCRFFNS	
Perf/S Casing/ Screen creen Liner Dia	Scrn/slot Slot # of Tele From To width length slots pipe s	
	Troin 10 Width length was pipe of	
		MECENIEN
		RECEIVED
		OCT V 1 /
		WATER RESOURCES DEPT
		SALEM, ORECON
		_
(8) WELL TESTS: N	Minimum testing time is 1 hour	
Yield gal/min Drawo	down Drill stem/Pump depth Duration (hr)	0
		Comments/Remarks
		FROM 445' - 18' - 279 BAGS BENTONITE
Water Quality Conc	·	FROM 18' TO SURFACE - 6 BAGS CEMENT USED TO ABANDON
From To	Description Amount Units	WITH SPECIAL STANDARDS APPROVAL FROM K. BYRD. TDS 363 PPM
		PRE-ABANDONMENT STATIC 351'.