## STATE OF OREGON

WATER WELL REPORT (as required by ORS 537.765)

## ILL SOFT

## negewed

CN/35E/28H

PLEASE TYPE or PRINTIN INT 1992

(for offzere use only)

(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name HONCH Phillips	County SE4 SE4 of Section 25
Address	Township Range 35 F w
City Millia Frenchite State Origin	(Township is North or South) (Range is East or West)  Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	Tax Lot Lot Block Subdivision  MAILING ADDRESS OF WELL (or nearest address)
New Welt ⊠ Deepening □ Reconditioning □ Abandon □	WATERWAY ADDITION OF A SEPT (Or Hearest address)
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic M Industrial Municipal	Depth at which water was first found 65/1
Thermal:	Static level 25 ft below land surface. Date 12-1.
Other:	Artesian pressure lbs. per square inch. Date
Cable Bored Piezometric Grounding Test	
(5) CASING INSTALLED: Steel  Plastic	(12) WELL LOG: Diameter of well below casing
Threaded Welded W	Formation: Describe color texture grain size and structure of metavioles and a surface
O Diam from The ft. to Colift. Gauge OSS	and nature of each stratum and aquifer penetrated, with at least one entry for each change
TINER INSTALLED. HARAGE SEC. 3.50	formation. Report each change in position of Static Water Level and indicate princi, water-bearing strata.
Plastic N	Number of the second se
Threaded Welded Threaded Welded Threaded Gauge 5/14/6. Plk	MATERIAL From The SWL
Diam. from	1105.110
(6) PERFORATIONS: Perforated? Yes \( \subseteq \) No	- Douldon 12/ Shive 13 13 22
Size of perforations in. by fig. (3/V) in.	Braider 10 Bru Mad 1/3 16 12
perforations from 256 ft to 357 ft	Concerted Grave Briv 46 94 35
perforations from ft. to ft.	GLEX MUSY SIT (10B) 94 161 35
perforations from ft. to ft.	
(7) SCREENS: Well screen installed?   Yes No	Compated Grave BIN 10/ 294 35
Manufacturer's Name	Compated Gravel Ring 2017 35
TypeModel No.	Gravel like 34, 3-12
Diam. Slot Size Set from ft. to ft.	15 15 15 15 15 15 15 15 15 15 15 15 15 1
Diam. Slot Size Set from ft. to ft.	
(8) WELL TESTS:  Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom?	
Yield: 120 gal./min. with 195 ft. drawdown after // hrs.	
Air test gal./min. with drill stem at ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encounteredft.	
(9) CONSTRUCTION: Special standards: Yes \( \sigma \) No \( \sigma \)	Date work started 6-15-87/completed 85-89
Well seal-Material used Lize 14 TE	Date well drilling machine moved off of well / ~//6 1987
Well sealed from land surface toft.	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal in.	This well was constructed under my direct supervision. Materials used an
Diameter of well bore below seal	information reported above are true to my best knowledge and befief.
Amount of sealing material pounds pounds	[Signed] Date 2. 19 5
How was cement grout placed?	(bonded) Water Well Constructor Certification:
Them Butter To Tak	1
	Bond Issued by: Surety Company Names
Was pump installed? Type HP Depth ft.	On behalf of
Was a drive shoe used? X Yes No Plugs	(type or print name of Water Well Constructor)
Did any strata contain unusable water?	This well was drilled under my jurisdiction and this report in true to the
	best of my knowledge and belief:
Method of sealing strata off	(Signed)(Water Well Constructor)
Was well gravel packed?   Yes S No Size of gravel:	(Water Well Constructor) (Dated)
Gravel placed from ft. to ft.	