NOTICE TO WATER WELL CONTRACTOR GEVEN The original and first copy of this report are to be filed with the MAR 2 - 19WATER WELL REPORT APR 4 - 1972

STATE ENGINEER, SALEM, OREGON PROTE ENGINEERS type or print TATE ENGINEER OF SALEM. OR GO NOT Write above this line SALEM. OR GO NOT WRITE PERMIT NO.

(1) OWNER:	(11) LOCATION OF WELL:			
Name STEVE MONOGIOUS 568	County CMATILLA Driller's well number			
Address PENDLETON, OPEGON	N 14 14 Section 15 T. 2 N R. 3 2 E W.M.			
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner			
New Well ☑ Deepening □ Reconditioning □ Abandon □	East 300' west 700'			
If abandonment, describe material and procedure in Item 12.				
		<del> </del>		<u> </u>
Rotary Driven Domestic M Industrial D Municipal D	(12) WELL LOG: Diameter of well below casing			
Cable	Depth drilled 280 ft. Depth of comple	eted well	280	) ft.
CASING INSTALLED: Threaded   Welded   Welded   Welded   Threaded   Threaded   Welded   Threaded   T	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of form in position of Static Water Level as drilling pro	m and aq ation. Re	quifer pe port eac	netrated, h change
" Diam. from ft. to ft. Gage	MATERIAL	From	То	SWL
ft. Gage ft. Gage	Soil	0	5	
PERFORATIONS: Perforeted?   Ves. 18 No.	Soil & Basalt, Broken	5	7	
Totalatia. El Tes Million	BASALT BLACK	7	38	<del></del>
Type of perforator used	BASALT! RED WITH CLAY	38	45	
Size of perforations in. by in.	BASALT, BRN	45	67	
perforations from ft. to ft.	BASALT, RED , Porous	67	77	
perforations from ft. to ft.	BASALT, BROWN, Porous	77	90	F1.7
perforations from ft. to ft.	BASALT, BRN, RED. "	90	103	
perforations from ft. to ft.	BASAUT, GREY, SOFT	103	143	
perforations from	BASAUT, BRN& RED W CLAY	143	178	
(7) SCREENS: Well screen installed? Tives No No.	BASALT GREY	178	208	
West Boston Missander [ ] Tes [2] 140	BASALT', RED, POROUS	208	216	
Manufacturer's Name  TypeModel No	BASALT, BROWN	216	220	
Diam. Slot size Set from ft. to ft.	BASALT, BROKEN, RED	220		(CAVING
Diam. Slot size Set from ft. to ft.	BASAUT, GREY	223	258	
(8) WATER LEVEL: Completed well.	BASALT, RED, BROWN, Brown	258	278	(WATER)
Static level 2/0 ft. below land surface Date 2/23/72	BASALT, GREY	278	280	
sian pressure lbs. per square inch Date		<del> </del>		
(9) WELL TESTS: Drawdown is amount water level is				
iowered below static level				
Was a pump test made? Yes No If yes, by whom? PUMP	Work started 2-15-72 19 Complete	00 2 -1	0 4	
Yield: 50 gal./min. with 50 ft. drawdown after 23 hrs.	Work started 2-15-72 19 Completed 2-18-72 19  Date well drilling machine moved off of well 2-18 1972			
" " " "	Drilling Machine Operator's Certification:	<u> </u>	-	
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my di	rect supe	ervision.	Mate-
Artesian flow g.p.m. Date	rials used and information reported above are true to my best knowledge and belief.			
Temperature of water 64 ° Was a chemical analysis made? ☐ Yes ☐ No	[Signed] M. Juil Date Job 25, 1972			
(10) CONSTRUCTION:	,		2	
Well seal-Material used POTTLAND CEMENT (7 SACKS)	Drilling Machine Operator's License No. 709			
Depth of sealft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off?   Yes   No Depth	true to the best of my knowledge and belief.			
Was a drive shoe used? 🗌 Yes 🙀 No	NAME PROJECT: Corporation (Type or print)			
Did any strata contain unusable water?   Yes No	Ala Quinu a			
Type of water? depth of strata	Address A. 3 OX 131-B			
Method of sealing strata off	[Signed]			
Was well gravel packed?   Yes No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 5/2 Date Leb 25 1972			