UMAT 57218

UMAT 57218

STATE OF OREGON

WATER SUPPLY WELL REPORT

(as required by ORS 537.765)

WELL I.D. # L 106757 START CARD # 208463

Instructions for completing this report are on the last page of this form.					
(1) LAND OWNER Koppany. Well Number	(9) LOCATION OF WELL County Limetile	L by legal	description:	ongitude	<u>.</u>
Address 80014 Riker Lane	Township 4N	Nor S Rang	29E	E or W.	
City Hermiston State OR zip 97838			SWI	14	
(2) TYPE OF WORK	Tax Lot 4000 Lot	Bloc	kSu	bdivision_	
Driew Well Deepening Alteration (repair/recondition) Abandonment	Street Address of Well (or r	earest addges	Hope !	Lane	
(3) DRILL METHOD: Brotary Air Rotary Mud Cable Auger	(10) STATIC WATER LE	501	97838	<u> </u>	===
Other	ft. below lar			Date 2	17-13
(4) PROPOSED USE:	Artesian pressure	lb. per	square inch	Date	
Domestic Community Industrial Irrigation	(11) WATER BEARING 2				
☐ Thermal ☐ Injection ☐ Livestock ☐ Other	5-1	£	53		
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first	round			
Special Construction approval Yes No Depth of Completed Well ft. Explosives used Yes No Type Amount	From	То	Estimated Flow Rate		SWL
HOLE SEAL	53	56	100	<u>'</u>	16
	[· · · · · · · · · · · · · · · · · · ·				
Diameter From To Sacks or pounds Sacks or poun			 		+
8" 20 56					
	(40) ************************************				1
Howwas seat placed: Mothod DA DB DC. DD DE	(12) WELL LOG: Ground Elev	etion			
Dother foured 3/2" bentonite chips	Orodila Dick				
Backfill placed fromft. toft. Material	Material		From	То	SWL
Gravel placed fromft. toft. Size of gravel	Sandy Soil		_0_		-
(6) CASING/LINER:	Sand			543	
Diameter From To Gauge Steel Plastic Welded Threaded Casing: 7 / 56 -250 P	Grave/	-MRY	OWS	56	W.R
	- SECEN	ED D.			
	HEO	/(16)	1113		
	· · · · · · · · · · · · · · · · · · ·	19	0.0		+
Liner	180				+
		SALEN	OF		+
Drive Shoe used Inside Doutside None					+
Final location of shoe(s) 56	D	ECEIVE	D BA OM	RD-	+
(7) PERFORATIONS/SCREENS: Perforations Method		COLIV			1
☐ Screens TypeMaterial		A110	1 3 2013		1
Slot Tele/pipe		HUU	1 0 000		
From To size Number Diameter size Casing Liner					
		S	LEM, OR		
(8) WELL TESTS: Minimum testing time is 1 hour	Date started 7-16-			7-17	<u>-/3</u>
□ Pump □ Bailer	(unbonded) Water Well Constr				
Yield gal/min Drawdown Drill stem at Time	I certify that the work I perfo ment of this well is in compliance				
100 56 1 hr.	standards. Materials used and inf				
	knowledge and belief.		WWC Num	nher	
	Signed)ale	
Temperature of water 580 Depth Artesian Flow Found	(bonded) Water Well Construct	tor Certifica	tion:		
ras a water analysis done: les By whom	I accept responsibility for the	e constructio	n, alteration, or ab		
Did any strata contain water not suitable for intended use?	performed on this well during the performed during this time is in o				
Salty Muddy Odor Colored Other	construction standards. This repo	n is true to t	here of my know	wledge and	beliefo
Depth of strata:	1 17-11	4/-	WW/SNum	iber	1/8
	Signed Signed	7	D D	ate \$-/	<u> </u>