

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

UMAT 57469

WELL I.D. LABEL# 116912 START CARD # 1025319 ORIGINAL LOG #

(1) LAND OWNER Owner Well I.D. First Name Last Name Company PLISKA INVESTMENTS, LLC Address P.O. BOX 1429 City CLACKAMAS State OR Zip 97015-1429

(2) TYPE OF WORK [X] New Well [] Deepening [] Conversion [] Alteration (complete 2a & 10) [] Abandonment (complete 5a)

(2a) PRE-ALTERATION Dia + From To Gauge Stl Plstc Wld Thrd Casing: Material From To Amt sacks/lbs Seal:

(3) DRILL METHOD [X] Rotary Air [] Rotary Mud [] Cable [] Auger [] Cable Mud [] Reverse Rotary [] Other

(4) PROPOSED USE [] Domestic [] Irrigation [] Community [X] Industrial/ Commercial [] Livestock [] Dewatering [] Thermal [] Injection [] Other

(5) BORE HOLE CONSTRUCTION Special Standard (Attach copy) Depth of Completed Well 440.00 ft.

Table with columns: Dia, From, To, Material, SEAL From, To, Amt, lbs. Rows include Bentonite Chips and Cement.

How was seal placed: Method [X] A [X] B [] C [] D [] E [X] Other POURED BENTONITE Backfill placed from ft. to ft. Material Filter pack from ft. to ft. Material Size Explosives used: [] Yes Type Amount

(5a) ABANDONMENT USING UNHYDRATED BENTONITE Proposed Amount Actual Amount

(6) CASING/LINER Casing Liner Dia + From To Gauge Stl Plstc Wld Thrd Shoe [X] Inside [X] Outside [X] Other Location of shoe(s) 5 Temp casing [] Yes Dia From To

(7) PERFORATIONS/SCREENS Perforations Method Screens Type Material Perf/ Casing/ Screen Screen Liner Dia From To Scrm/slot width Slot length # of slots Tele/ pipe size

(8) WELL TESTS: Minimum testing time is 1 hour [] Pump [] Bailer [X] Air [] Flowing Artesian Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Temperature 67 °F Lab analysis [] Yes By Water quality concerns? [] Yes (describe below) TDS amount From To Description Amount Units

(9) LOCATION OF WELL (legal description) County UMATILLA Twp 4.00 N N/S Range 28.00 E E/W WM Sec 33 SE 1/4 of the NW 1/4 Tax Lot 104 Tax Map Number Lot Lat Long Street address of well Nearest address 77514 S HWY 207 HERMISTON, OR

(10) STATIC WATER LEVEL Date SWL(psi) + SWL(ft) Existing Well / Pre-Alteration Completed Well 1/15/2015 295 Flowing Artesian? Dry Hole?

WATER BEARING ZONES Depth water was first found 55.00 SWL Date From To Est Flow SWL(psi) + SWL(ft) 1/8/2015 55 90 50 40 1/12/2015 223 290 30 60 1/15/2015 408 425 50 295

(11) WELL LOG Ground Elevation Material From To SAND/GRAVEL 0 20 BROWN CLAY/GRAVEL 20 90 TAN SANDY CLAY 90 115 BLACK BASALT 115 223 BLACK BASALT W/GREEN CLAYSTONE 223 290 BLACK BASALT 290 408 BLACK BASALT W/GREEN CLAYSTONE 408 425 BLACK BASALT 425 440 RECEIVED BY OWRD JAN 22 2015 SALEM, OR

Date Started 1/5/2015 Completed 1/15/2015 (unbonded) Water Well Constructor Certification I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. License Number 1735 Date 1/19/2015 Signed CHAD COURTNEY (E-filed)

(bonded) Water Well Constructor Certification I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. License Number 1881 Date 1/19/2015 Signed GARRY L ZOLLMAN (E-filed) Contact Info (optional) GARRY ZOLLMAN

WATER SUPPLY WELL REPORT - continuation page

UMAT 57469

WELL I.D. LABEL# L

116912

START CARD #

1025319

ORIGINAL LOG #

(2a) PRE-ALTERATION

Dia	+	From	To	Gauge	Stl	Plstc	Wld	Thrd

Material	From	To	Amt	sacks/lbs

(5) BORE HOLE CONSTRUCTION

BORE HOLE			SEAL			sacks/lbs	
Dia	From	To	Material	From	To	Amt	lbs
			Cement	125	138	5	S
						Calculated	5
						Calculated	
						Calculated	
						Calculated	

FILTER PACK

From	To	Material	Size

(6) CASING/LINER

Casing Liner	Dia	+	From	To	Gauge	Stl	Plstc	Wld	Thrd

(7) PERFORATIONS/SCREENS

Perf/ Screen	Casing/ Liner	Screen Dia	From	To	Scrn/slot width	Slot length	# of slots	Tele/ pipe size

(8) WELL TESTS: Minimum testing time is 1 hour

Yield gal/min	Drawdown	Drill stem/Pump depth	Duration (hr)

Water Quality Concerns

From	To	Description	Amount	Units

(10) STATIC WATER LEVEL

SWL Date	From	To	Est Flow	SWL(psi)	+ SWL(ft)

(11) WELL LOG

Material	From	To

Comments/Remarks

TUBEX DRIVE SHOE AT 138' WAS MILLED OFF. 6 INCH FLOAT SHOE WAS USED TO CEMENT THE 6 INCH CASING IN PLACE. THREADED 6 INCH DRIVE SHOE AT 5'.