STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765)

UMAT RFC 8 2 2 1994

JUL 2 0 1994

60/35e/240

(as required by ORS 537.765) WATELEASE TYPE of	7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	(for official use only)
(1) OWNER:	(10) LOCATION OF WELL by lega	
Name Tyrone KINZEK	County UMattila SEXSUN	of Section 2 9 of
Address RT3 Box 158 W	Township (Township i North) r South)	Range is East or West)
City Milton Freehotek State Okeston	Tax Lot Lot Block Subdivision	Tuniço i Sanosor (1000)
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)	3 BOKISTW
New Well	do Firm of City and and	Rogson 92862
If abandonment, describe material and procedure in Item 12.	· .	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLET	ED WELL:
Rotary Air Driven Domestic Industrial Municipal Thermal:	Depth at which water was first found Static level ft. below	land surface. Date 5-209
Rotary Mud Dug Irrigation Withdrawal Reinjection Other:		square inch. Date
Cable Bored Piezometric Grounding Test		1 4
5) CASING INSTALLED: Steel Plastic	Depth drilled 95 Diameter of well below	v casing
Threaded Welded Welded Work of the Gauge 257	Formation: Describe color, texture, grain size and structure and nature of each stratum and aquifer penetrated, with at I	
•	formation. Report each change in position of Static Wat	
"Diam. from	water-bearing strata.	
LINER INSTALLED: Steel Plastic Welded Welded	MATERIAL	From To SWL
45" Diam. from 80 ft. to 95 ft. Gauge 80140	O- BHNSILT	022
	Gravel Loose Sond	2234 10
(6) PERFORATIONS: Perforated? X Yes \(\square\) No	Cemented Gravel	34 95 10
Size of perforations in.		
periorations from	•	
perforations from		
perforations from		
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name		
Type Model No		
Diam. Slot Size Set from ft. to ft.		
Diam. Set from ft. to ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom?	4.	
Yield: gal./min. with ft. drawdown after hrs.	A STATE OF THE STA	
<u> </u>	**************************************	
Air test 200 gal./min. with drill stem at 80 ft. / hrs.		<u> </u>
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Pemperature of water 52 Depth artesian flow encountered ft.	Date work started 5-/4-94 /complete	ed 5-20-94
(9) CONSTRUCTION: Special standards: Yes \(\text{No.} \)	Date well drilling machine moved off of well	5-21-94 19
Well seal—Material used Cement	(unbonded) Water Well Constructor Certific	
Well sealed from land surface toft.	This well was constructed under my direct sup	
Diameter of well bore to bottom of seal in.	information reported above are true to my best known	
Diameter of well bore below seal in.	FC:	D-4- 10 ·
Amount of sealing material sacks pounds	[Signed]	Date, 19
How was cement grout placed?	(bonded) Water Well Constructor Certification:	
	Bond Issued by: Sw	rety Company Name)
Was pump installed?	On behalf of Pro - Orill Tuc	
Was a drive shoe used? Yes \(\subseteq \text{No} \) Plugs	(type or point name of Water Well Comptructor)	
Did any strata contain unusable water? Yes No	This well was drilled under my jurisdiction a	and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:	4756
Method of sealing strata off	(Signed) Water ell Construction	tor) // / /
Was well gravel packed? Yes Size of gravel:	(Dated) 5-25-94	
Gravel placed from ft. to ft.		