DEC 3 1 1980 State Well No. 21 WATER RESOURCES DEPARTMENT, JUL 17 1980 TATE OF OREGON SALEM, OREGON 97310 (Please type or print) within 30 days from the date of well completion. WATER RESOURCES DEPT above this line? RESOURCES DEPT No. SALEM. OREGON CALEM OREGAN (10) LOCATION OF WELL: (1) OWNER: County Um AT/LLA Driller's well number 14 Su) 14 Section 17 T. 2N R. 32F Bearing and distance from section or subdivision corner (2) TYPE OF WORK (check): New Well Deepening Reconditioning Abandon | If abandonment, describe material and procedure in Item 12. (11) WATER LEVEL: Completed well. (3) TYPE OF WELL: (4) PROPOSED USE (check): Depth at which water was first found Driven [] Static level 200 ft. below land surface. Date Domestic | Industrial | Municipal | Jetted [7] Bored | Irrigation Test Well | Other Artesian pressure lbs, per square inch. Date (5) CASING INSTALLED: Threaded | Welded (12) WELL LOG: Diameter of well below casing ... 16 " Diam. from +2 ft. to -138 ft. Gage 250 Depth drilled 920 ft. Depth of completed well ______ ft. to ______ ft. Gage _____ Formation: Describe color, texture, grain size and structure of materials; " Diam. from _____ft. to _____ft. Gage and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata. (6) PERFORATIONS: Perforated? | Yes | No. Type of perforator used MATERIAL SOIL Size of perforations in. by perforations from _____ ft. to _____ ft. CLOY X G.REVEL (BO BASALT Black 130 225 perforations from _____ ft. to _____ ft. 225 Red 233 perforations from ft. to ft. 233 267 Blech (7) SCREENS: Well screen installed? | Yes | No 267 Red 283 Manufacturer's Name 283 Black 352 Model No. R Lech 352 **380** Diam. Slot size Set from 11 525 528 Diam. Slot size Set from 11 528 Blach 566 é. 226 Red 607 Drawdown is amount water level is lowered below static level (8) WELL TESTS: LL BLACK W/35 607 621 a pump test made? Yes | No If yes, by whom? 127 NO 621 Black 785 Yield: 700 gal./min. with 250 ft. drawdown after BLZCK 785 795 795 825 843 875 **743** gal./min. with ft. drawdown after er test hrs. 875 BLack w/ Ren g.p.m. Temperature of water & Depth artesian flow encountered, Work started 5-10 19 8 C Completed 1980 Date well drilling machine moved off of well 19 5 (9) CONSTRUCTION: Well seal-Material used PORTLEND COMENT Drilling Machine Operator's Certification: 138 This well was constructed under my direct supervision. Well sealed from land surface to Materials used and information reported above are true to my Diameter of well bore to bottom of seal 17/2 in. best knowledge and belief. [Signed] (Ordling Machine Operator) Date 5-25 1980 Number of sacks of cement used in well seal ______ sacks Drilling Machine Operator's License No. 233 How was cement grout placed? TRemie Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Was a drive shoe used? No Plugs Size: location Name 7 Did any strata contain unusable water?

Yes depth of strata Address Type of water? Method of sealing strata off Was well gravel packed? [] Yes PNO Size of gravel: Contractor's License No. 544 Date ft. to

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this represent the original and first copy of this represent the water well report CE Water well report CE VED

are to be filed with the