NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report

are to be filed with the

WATER RESOURCES DEPARTMENT, UMAT SALEM, OREGON 97310 within 30 days from the date of well completion.

AMENDED WELL REPORT

State Well No

STATE OF OREGON AP (Do not write above this line) ESOURCES DEPT,

(1) OWNER:	(10) LOCATION OF WELL:
Name KOBERT PETRIK	County WM WIGHA Driller's well number 01-78
Address P++2 Box 20	** ** ** ** * * * * * * * * * * * * *
(2) TYPE OF WORK (shall)	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven	Depth at which water was first found ft.
Cable	Static level 200 ft. below land surface. Date /-1/-72
Dug Bored Irrigation Fest Well Other	Artesian pressure lbs. per square inch. Date
threaded Welded	(12) WELL LOG: Diameter of well below casing
ft. to ft. Gage	Depth drilled 1086 ft. Depth of completed well 1086 ft.
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	DEEPENING FROM 832 Fr.
perforations from ft. to ft.	
perforations from ft. to ft.	CUTTINGS FROM 811 832
perforations from ft. to ft.	MED. GREY BASALT 832 870
(7) SCREENS: Well screen installed? Yes No	BROKEN KED " 970 893 BROKEN GOEV " 893 005
Manufacturer's Name	BROKEN GREY " 893 905 HARD " " 905 915
Type Model No.	BROKEN Pro " 915 970 water
Diam Slot size Set from ft. to ft.	MED HARD " " 970 1001
Diam. Slot size Set from ft. to ft.	GREY " 1001 1020
(8) WELL TESTS: Drawdown is amount water level is bewered below static level	HARD GREY " 1020 1058
Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)	BROKEN RED " 158 1080 water
	HARO GREY " 1080 1086
" " " "	
Dellar test	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started /-// 19 78 Completed /-/5 19 78
(9) CONSTRUCTION:	Date well drilling machine moved off of well /-/5 1978
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] All Wille Date 2-2, 19.78
Number of sacks of cement used in well seal sacks How was cement grout placed?	Drilling Machine Operator's License No. 886
G	
S. S	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? 🗌 Yes 🗍 No Plugs Size: location ft.	Name MALLACE WELL DRIG CO.
Did any strata contain unusable water? Yes No	(Kerson, firm or corporation) (Type or print)
Type of water? depth of strata	Address FENDETTIN CREI 9780
Method of sealing strata off	[Signed] Signed]
Was well gravel packed? [Yes] No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. toff	Contractor's License No. 523 Date 2-2 10.78