NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310
within 30 days from the date
of well completion

WATER WELL REPORT CEIVED

STATE OF OREGON

FEB 10 1981 State Well No. 2N-324-200c (Please type or prevATER RESOURCES SDEPTermit No.

(Do not write above this line SALEM, OREGON

<del></del>		
(1) OWNER:	(10) LOCATION OF WELL:	
Name WILLIAM HUTTON	County UMSTILLA Driller's well number	
Address 1034 NW 1274	Sw 14 SE 14 Section 20 T. 2N R. 32E W.M.	
Pendleton  (2) Type of work (about)	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well  Deepening  Reconditioning  Abandon  If abandon  If abandonment, describe material and procedure in Item 12.		
	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 540 ft.	
Cable   Jetted   Domestic   Industrial   Municipal	Static level 400' ft. below land s	urface. Date (-14-8)
Dug   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square	e inch. Date
(5) CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below cosing 738	
" Diam. from +2 ft. to -18 ft. Gage 250	The state of well below cashing	
" Diam. fromft. toft. Gage		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur	n and aquifer penetrated
(6) PERFORATIONS: Perforated?   Yes Proposition 1	with at least one entry for each change of format position of Static Water Level and indicate prin	ion. Report each change in
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	Soll	0 3
perforations fromft. toft.	GREVEL CRAENTED	3 270
perforations from ft. to ft.	BASALT BROWN	270 285
perforations fromft. toft.	11 COREY	285 340
(7) SCREENS: Well screen installed?   Yes	n ReD	340 385
Manufacturer's Name	- " GREY	385 490
Type Model No.		490 510
Diam Slot size Set from ft. to ft.	- G/XE/	510 540 40 560
Diam. Slot size Set from ft. to ft.	" BROWN -	560 570
WELL TESTS: Drawdown is amount water level is	1 GREY	570 575
AIR lowered below static level		
was a number test made? Wes I No If yes, by whom? DRILLER		
Yield: 40 gal./min. with 120 ft. drawdown after / hrs.		
" " " " " " " " " " " " " " " " " " "		
" " "		
errer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.		
Temperature of water 🔑 Depth artesian flow encountered ft.	Work started 1 - 9 198/ Completed	1 /-14 1987
(9) CONSTRUCTION:	Date well drilling machine moved off of well	1-14 1981
Vell seal-Material used PORTIZNO COMENT	Drilling Machine Operator's Certification:	
Vell sealed from land surface to 18 ft.	This well was constructed under my direct supervision	
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore below seal	[Signed] Jany Buy Date 1-14 1981	
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)  Drilling Machine Operator's License No. 933	
Iow was cement grout placed? TROMIE	Drinnig Wachine Operator's License No	
T. CONT. CON	Water Well Contractor's Certification:	
	This well was drilled under my jurisdiction and this report is	
Vas a drive shoe used?  Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.  Name Lany Burd Well Dulling Inc.	
ype of water? depth of strate	(Person, firm or corporation) (Type or print)	
ype of water?depth of strate  Iethod of sealing strata off	Address 5543 S H. Douglas	. Rendleton or
	- [Signed] Jan Burd	
	(Water Well Contrac	etor)
ravel placed from ft. to ft.	Contractor's License No. 544 Date	1-17 , 190/
(USE ADDITIONAL SHEETS IF NECESSARY)		