NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

KEULIVEU WATER WELL REPORT DE 6 1 2 1973
State Well No. STATE OF OREGON
(Please type or print) STATE ENGINEER
(O) not write above this line) SALEM, OREGON

019	<u> </u>	
(1) OWNER:	(10) LOCATION OF WELL:	
Name Lawrence Behrenz	County Umatilla Driller's well number	
Address R. I Box 523-0 Hermiston, Ore. 97838	34 34 Section 8 T. 4N	r. 28E w.m.
(A) THE AT WART (1 1)	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 94 ft.	
Rotary Driven Domestic H Industrial Municipal Domestic	Static level 58 ft. below land surface. Date I2-6-73	
Cable Jetted Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date	
(5) CASING INSTALLED: Threaded Welded F	(12) WELL LOG: Diameter of well h	6
	Depth drilled 154 Depth of completed well 154 ft.	
	Departured 10. Depart of completed well 47.	
	Formation: Describe color, texture, grain size a and show thickness and nature of each stratur	
	with at least one entry for each change of format	tion. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator used	MATÉRIAL	From To SWL
Size of perforations in. by in.	surface sand brown	0 3
perforations from ft. to ft.	ashy soil	3 I2
perforations fromft. toft.	gravel	7 12 12 18
perforations from ft. to ft.	clay yellow	18 94
12	rock brown soft	01 770 50
(7) SCREENS: Well screen installed? Yes No	rock black soft	TZ0 T54 50
Manufacturer's Name	TOCK DISCK SOLO	132 134 3
Type Model No	· · · · · · · · · · · · · · · · · · ·	
Diam. Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ☐ Yes ☑ No If yes, by whom?		
Yield: gal./min. with ft. drawdown after hrs.		
n n n	·	
27/02		
411	<u> </u>	•
test 30 gal./min. with 62 ft. drawdown after 2 hrs.		
Artesian flow g.p.m.		
mperature of water Depth artesian flow encountered ft.	Work started I2-5 19 73 Complete	ed <u>T2-6</u> 19 73
(9) CONSTRUCTION:	Date well drilling machine moved off of well	I2-7 19 73
Well seal—Material used cement	Drilling Machine Operator's Certification:	
Well sealed from land surface to 20 ft.	This well was constructed under my	direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported best knowledge and belief	above are true to my
Diameter of well bore below seal in.		Date <u>12-70</u> , 1973
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No	200
Brand name of bentonite		· · · · · · · · · · · · · · · · · · ·
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:	
of waterlbs./100 gals.	This well was drilled under my jurisdi	
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	true to the best of my knowledge and bel	161.
Did any strata contain unusable water? Yes 1 No	Name Allison Drilling Co. (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address R. 2 Box 309-0 Hermisto	
Method of sealing strata off	KI Qui	
Was well gravel packed? ☐ Yes 💆 No Size of gravel:	[Signed] 1.40. (Water Well Contr	actor)
		2-TO 73
Gravel placed from ft. to ft.	Commacion a micense 140 Date	, 1J