NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGONAUG 191981

STATE OF OREGONAUG 191981 State Well No. 315-166.

(Please type WATER RESOURCES DERT Permit No. not write above this like. OREGON deepened (Do not write above this line) EM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name CURT ALEXANDER	County UM2TILLA Driller's well number
Address 4239 SW BROSDLENE	Su 14 Nu 14 Section 21 T. 2N R. 32 8 W.M.
PENDLETON	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	- Control
New Well ☐ Deepening	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 274 ft.
Rotary Driven Domestic Industrial Municipal Domestic	Static level 160 ft. below land surface. Date 8-4-8/
Dug 🗌 Bored 🗋 Irrigation 🗎 Test Well 🖂 Other 🖂	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(10) WITH T T O C
The Diam fromft. toft. Gage	Depth drilled 171 44 Depth of several day
1V 1" Diam. from ft. to ft. Gage	12, 13, 13, 13, 13, 13, 13, 13, 13, 13, 13
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated?  Yes Ano.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	GREY BESELT 239 254
perforations from ft. to ft.	BROWN 1 254 259
perforations from ft. to ft.	Red SCORIA 259 269
perforations from ft. to ft.	GRPY B252LT 269 274
(7) SCREENS: Well screen installed?	BROWN 1, 274 278
Manufacturer's Name	Black 11 278 280
Type	BROWN " 280 310
Diam. Slot size Set from ft. to ft.	BROWN 11 330 355
Diam. Slot size Set from ft. to ft.	370 33
	BLE CIT " 355 360
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a sump test made? Des D No If yes, by whom? DRILL-Q	
Yield: 40 gal./min. with 200 ft. drawdown after I hrs.	
20 " 120 " 1 "	
" " " " " " " " " " " " " " " " " " " "	
Bailer test gal./min, with ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water 62 Depth artesian flow encountered	G rati
(9) CONSTRUCTION:	Work started $(8-4-8)$ 19 Completed $(7-5-8)$ 19  Date well drilling machine moved off of well $(8-8-8)$ 19
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision
Diameter of well bore to bottom of sealin_	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below sealin.	
Number of sacks of cement used in well sealsacks	[Signed] Aug Burel Date 8-6, 198/
How was cement grout placed?	Drilling Machine Operator's License No. 549
	Water Well Contractor's Certification:
The second secon	
Was a drive shoe used? [] Wes [] No Pluce	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.  Did any strata contain unusable water? ☐ Yes ☐ No	Name LERRY BURD WELL DRILLING INC
	(Person, firm or corporation) (Type or print)
Method of sealing strate off	Address 5543 Sw. Dougles Peubleton
	[Signed] Yon Burg
	(Water Well Contractor)
Gravel placed fromft. toft.	Contractor's License No. 544 Date 8-6-8, 19