NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

)State	Well	No.	6N/35E-201
,			

)State	Well No. 6N/35E-201						
/	State	Permit No.						
	<u>+</u> -	·			> 444			

) OWNER:	(10) LOCATION OF WELL:			
Name PAT VOLLMER	County UMaTILL A Driller's well number			
Address MILTON FREGUETER R-ROUTS	NU 14 14 Section 20 T. 6NR. 35 F. W.M.			
	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	7A7 COX 400			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found //O ft.			
Rotary Driven Domestic Industrial Municipal				
Cable	Static level / C ft. below land surface. Date /-/8-1			
Dug Bored Irrigation	Artesian pressurelbs. per square inch. Date			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 7			
"Diam. fromft_fo/ft. Gage	Depth drilled 63 ft. Depth of completed well 763 ft.			
ft. Gage				
"Diam. from	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,			
DEDUCED A MICANO	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
PERFORATIONS: Perforated? Yes No.				
Type of perforator used	MATERIAL From To SWL			
Size of perforations in.	GRAVOL MEDIUM 200 263 70			
perforations fromft. toft.	<u> </u>			
perforations from ft. to ft.				
perforations from ft. to ft.				
(7) SCREENS: Well screen installed? Yes No	:			
Manufacturer's Name				
pe Model No.				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	RECEIVED			
(2) WELL TESTS. Drawdown is amount water level is				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	AUG3-1979 * * **			
Was a county test made? Yes No If yes, by whom? DRILLED	WATER RESOURCES DEPT			
mid: 200 + gal./min. with 50 ft. drawdown after / hrs.	SALEM, OREGON			
" " "	Onlin, Onegon			
" " " "				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.	99,8			
perature of water 50 Depth artesian flow encountered ft.	Work started 7-/7-7610 Completed 7-/8-78			
Seperature of water 10 Depart at testail flow encountered	Work started /-/7-7919 Completed /-/7-719			
(9) CONSTRUCTION:	Date well drilling machine moved off of well /8 - 29 19			
Well seal-Material used	Drilling Machine Operator's Certification:			
Well sealed from land surface to ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my			
Diameter of well bore to bottom of seal in.	best knowledge and belief.			
Diameter of well bore below seal in.	[Signed] Date 7-8, 1979			
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 933			
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator & Literature 110.			
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is			
of water lbs./100 gals.	true to the best of my knowledge and belief.			
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location #t.	Name John (Person, firm or corporation) (Type or print)			
any strata contain unusable water? Yes No	Da Vatt			
Type of water? depth of strata	Address (9 Address			
Method of sealing strata off	[Signed] Land Bung			
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 544 Date 7-78-79, 19			