REGEIVED APR 6 1961

File Original and First Copy with the STATE ENGINEER, SALEM, OREGON

ţ,

STATE ENGINEER WELL REPORT

UMAT 6203 State

6N/35 70Q

Ctata Danusii Ma

(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level
Address RIA & Millon Free water Ore.	Was a pump test made? Pres No If yes, by whom? - L, W, Marla? Yield: 250 gal./min. with 40 ft. drawdown after 3 brs
THE THE WALL TO	Yield: 25 () gal./min. with 4() ft. drawdown after 3 hrs
(2) LOCATION OF WELL: Lil. \$2	" " "
County Umatilla Owner's number, if any—	Bailer test gal./min. with ft. drawdown after hrs
SW 1/4 SE 1/4 Section 20 T. 6 N. R. 35 E.W.M.	Artesian flow g.p.m. Date
Bearing and distance from section or subdivision corner	Temperature of water √ / Was a chemical analysis made? ☐ Yes ☐ No
	(12) WELL LOG: Diameter of well inches
570 ft. North from apoint 680 ft.	Depth drilled 85 ft. Depth of completed well 85 ft
West from the Southeast Corner of the Southwest 1/4 of the Se 1/4	Formation: Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each
of Sec 20 Tp. 6 N. R. 35 E.W.M.	stratum penetrated, with at least one entry for each change of formation
	MATERIAL FROM TO
(3) TYPE OF WORK (check):	Top Soil + Clay 0 10
New Well Deepening Reconditioning Abandon Stabendonment, describe material and procedure in Item 11.	Conglomerate With Brownelay 10 16
- Mariatolinent, teseribe material and procedure in term 11.	Congrunerate Will provincial 10 16
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Cement Gravel (Brown) 16 30
Domestic Industrial Municipal Rotary Driven Cable Jetted	
Trigation Test Well Other Dug Bored	Conglomerate With Brownship 30 49
(6) CASING INSTALLED: Threaded □ Welded 中	
8 "Diam. from 0 ft. to 7/3" ft. Gage 5/16	Gravel With some mixed Sund 49 53
ft. to ft. Gage	Water Bearing Gravel
ft. to ft. Gage	With Very little
(7) PERFORATIONS: Perforated? ☑ Yes ☐ No	Mixed Black Sand 55 85
Type of perforator used HeeTylene TorTch.	
SIZE of perforations in. by in.	
per 1. perforations from 34 ft. to 57 ft.	
perforations from ft. to ft. 18 70 12 perforations from level, ft. to ft.	
78 10.72 Perforations from ft. to ft.	
perforations fromft. toft.	
(8) SCREENS: Well screen installed □ Yes 巨No Manufacturer's Name	
Type Model No	
Slot size Set from ft. to ft.	
Diam Slot size Set from ft, to ft,	Work started Jan 5 1961 Completed Jan 30 1961
(9) CONSTRUCTION:	(13) PUMP:
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	Manufacturer's Name
Gravel placed from ft. to ft.	Type: H.P.
Was a surface seal provided? Yes No To what depth? ft.	
Material used in seal— Did any strata contain unusable water? □ Yes 垺No	Well Driller's Statement:
Type of water? Depth of strata	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Method of sealing strata off	MALLOTT
(10) WATER LEVELS:	NAME COVE W 14 (1) (Person, firm, or corporation) (Type or print)
Static level 32 ft. below land surface Date Lon 3/6	Address P.T. # 2 Box III # Millon Free Water, Or
Artesian pressure lbs. per square inch Date	Driller's well number
Lag Accorded have	I MAM ATT
Log Accepted by:	(Well Driller)
[Signed] P D Avile Date 45, 19	License No. 265 Date fan. 31 , 1961
	1 /