## STATE OF OREGON

## WATER WELL REPORT (as required by ORS 537.765)

SEP 1 1994

Umat	- ,
6217	/

PLEASE TYPE or PRINT IN INK A. OREC	Start Cord	(Controlled use only)
--	------------	-----------------------

(1) OWNER:	(10) LOCATION OF WELL by legal description:  County Line Scale Mich of Section 33 of			
Name Cim WallSell	About See E of			
Address KI 2 BOX 226  City MITCH Floor NTOR State ORPHON.	Township (Township is North or South) (Range is East or West) WM.			
Ontilo	Tax Lot Block Subdivision			
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)			
New Well Deepening Reconditioning Abandon				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:			
Rotary Air Driven Domestic Industrial Municipal	Depth at which water was first found 68 ft.			
Thermal:	Static level 50 ft. below land surface. Date 9-7-90			
Other:	Artesian pressure lbs. per square inch. Date			
Cable D Bored Piezometric Grounding Test	(12) WELL LOG: Diameter of well below casing/O ''			
5) CASING INSTALLED: Steel Plastic	(12) WELL LOG: Diameter of well below casing			
Threaded Welded	Formation: Describe color, texture, grain size and structure of materials; and show thickness			
10 "Diam from + 1 ft. to 30 ft. Gauge 0250	and nature of each stratum and aquifer penetrated, with at least one entry for each change of			
ft. to ft. Gauge	formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
LINER INSTALLED: Steel  Plastic				
Timeaded □ Welded □	MATERIAL From To SWL			
8 Diam from 20 ft. to 180 ft. Gauge Sch 40	Blow Soil of Grove 1 0 2			
	Tan SITY Boulders 2 12			
(6) PERFORATIONS: Perforated? X Yes In No Livel	LOOSE Gravel Bry Silt 12 16			
6 7 2 perforations from 120 ft. to 182 ft.	Bin SIT Comented Bravel 16 22			
	Tows IT Comented Staves 22 68			
perforations from	Brown SITT COMENTED Grove 68 128 50			
perforations from ft. to ft.	Gley comented Stavel			
(7) SCREENS: Well screen installed?   Yes No	Clean water Bourney 128 180 50			
Manufacturer's Name	Brown SilT Loose Gravel 180 192 50			
Type				
Diam Slot Size				
Diam Slot Size Set from ft. to ft.				
Drawdown is amount water level is lowered				
(8) WELL TESTS:  below static level				
Was a pump test made?    Yes No If yes, by whom?				
Vield: gal./min. with ft. drawdown after hrs.				
u u u				
Air test $3\infty$ gal./min. with drill stem at $180$ ft. $2$ hrs.				
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
emperature of water 54 Depth artesian flow encountered ft.				
	Date work started 8-30-94 /completed 9-1-94			
(9) CONSTRUCTION: Special standards: Yes \( \text{No.} \)	Date well drilling machine moved off of well $9-7$ 19 94			
Well seal—Material used	(unbonded) Water Well Constructor Certification (if applicable):			
Well sealed from land surface to	This well was constructed under my direct supervision. Materials used and			
Diameter of well bore to bottom of seal	information reported above are true to my best knowledge and belief.			
Diameter of well bore below sealin.	[Signed], 19			
Amount of sealing materialsacks 🗶 pounds 🗆	[Signed] Date, 19			
How was cement grout placed?	(bonded) Water Well Constructor Certification;			
	Bond Issued by:			
II	(number) (Surety Company Name)			
Was pump installed? Type HP Depth ft.	On behalf of			
Was a drive shoe used? XYes \( \sum \) No \( \text{Plugs} \) No \( \text{Plugs} \) Size: location \(	(Distance)			
Did any strata contain unusable water?	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:			
Type of Water? depth of strata	The state of the s			
Method of sealing strata off	(Signed) (Vater Well Constructor)			
Was well gravel packed? Tes XNo Size of gravel:	(Dated) 9-7-94 (Valer well Constructor)			
Gravel placed from				