NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

UMAT 643

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

G-5970

State Well No. 2N/32E/22

State Permit No.

RECEIVED
SEP - 3 1975
WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:
Name RICHARD MILLER
Address TUTUILLA ROAD PENDLETON ORE

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:
Threaded ☐ Welded ☐
EXISTING Diam. from ft. to ft. Gage
..... " Diam. from ft. to ft. Gage
..... " Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☑ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a AIR pump test made? ☑ Yes ☐ No If yes, by whom? DRILLER
Yield: 50 gal./min. with 100 ft. drawdown after 1 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water 68° Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used EXISTING
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☑ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County UMATILLA Driller's well number 45-66
NE ¼ SE ¼ Section 22 T. 2N R. 32E W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 370 ft.
Static level 316 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8" to 317, 6" to 425
Depth drilled 108 ft. Depth of completed well 425 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
BASALT RED	317	325	
" BLACK	325	370	
" BROWN	370	400	206
" BLACK	400	410	
" BROWN SOFT	410	420	606
" BROWN HARD	420	425	

Work started 8-17 19 75 Completed 8-17 19 75
Date well drilling machine moved off of well 8-18 19 75

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Jerry Burd (Drilling Machine Operator) Date 8-18, 1975
Drilling Machine Operator's License No. 933

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name LARRY BURD WELL DRILLING (Person, firm or corporation) (Type or print)
Address P O Box 417 PENDLETON ORE
[Signed] Jerry Burd (Water Well Contractor)
Contractor's License No. 544 Date 8-18, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119