

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WATER WELL REPORT

MAY 4 1973

STATE OF OREGON FEB 2 1973

State Well No.

2N/32E-22

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date
of well completion.

STATE ENGINEER

(Please type or print)

STATE ENGINEER

State Permit No.

SALEM, OREGON

Do not write above this line

SALEM, OREGON

6-5963 #2

(1) OWNER:

Name LYLE FARLEY
Address 112 SE 10th
PORTLAND

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒

6" Diam. from 0 ft. to 19 ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☐ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " " " "
" " " " " "
Pump test 30 gpm gal./min. with ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 68° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used PORTLAND CEMENT
Well sealed from land surface to 19' ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 1 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County umatilla Driller's well number
SE 1/4 SE 1/4 Section 22 T. 2 N R. 32 W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 222 ft.
Static level 335 ft. below land surface. Date
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6" 1

Depth drilled ft. Depth of completed well 396 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Sand	0	4	—
Caliche White	4	5	—
Basalt Grey	5	38	—
green	38	44	—
grey	44	45	—
Red	45	98	—
grey	98	176 1/2	—
Red	176 1/2	186	—
grey	186	195	—
Rock Red	195	222	—
Basalt grey	222	290	—
Red	290	300	—
grey	300	396	—

Work started 1 - 2 1973 Completed 1 - 17 1973
Date well drilling machine moved off of well 1 - 18 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Don Dilligie Date 2-1-73
(Drilling Machine Operator)

Drilling Machine Operator's License No. 181

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name HARRY BIRD Well Drilling
(Person, firm or corporation) (Type or print)

Address PO Box 417

[Signed] Larry Bird
(Water Well Contractor)

Contractor's License No. 544 Date 1-29, 1973