NOTICE TO WATER WELL CONTRACTOR.

The original and first copy of this report
are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENTAPR 20 1981 STATE OF OREGON

SALEM, OREGON 97310

within 30 days from the APATER RESOURCES DEPT (Please type or print)

of well completion.

SALEM, OREGON not write above this line)

State Well No.

State Permit No.

SP*45656-119

(1) OWNER:	(10) LOCATION OF WELL:
Name Stawley F Druce	County Um Tilla Driller's well number
Address R2 Box 17A7	NE 14 NW4 Section 30 T. 6N R. 35E W.M.
MITON FreeWATER 99862	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Tax Lot 1200 628 F East bot Not
New Well ★ Deepening □ Reconditioning □ Abandon □	of Swight Corner
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 65 ft.
Rotary X Driven Domestic Industrial Municipal Domestic	Static level 50 ft. below land surface. Date 1, 121 19
Dug Bored I Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded Wel	(12) WELL LOG: Diameter of well below casing 159
	Depth drilled // ft. Depth of completed well /63 ft.
ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated.
PERFORATIONS: Perforated? Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Bulders & sandsoil 0 10
perforations fromft. toft.	Brn
perforations from ft. to ft.	hoerd from 2-3" Ports 10 38
perforations from ft. to ft.	Jelinhard from Balders 38 65 65
(7) SCREENS: Well screen installed? Yes K No	Blue clay, b5 68
Manufacturer's Name	- Tyrn hand frances
Type Model No.	Hock 2-6" 68 109 65
Diam. Slot size Set from ft. to ft.	yellack sonaly clay 109 188
Diam. Slot size Set from ft. to ft.	BO. 6 - 0116 100 1016 65
	- Bololes 3-8" Bon 138 166 65
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	- nousiper
Was a pump test made? Yes I No If yes, by whom Mouller	
Yield: 250 gal./min. with /D ft. drawdown after 2 hrs.	
" " "	
n n n n	
Bailer test gal./min. with ft, drawdown after hrs.	22
And the management of the second of the seco	
perature of water 5/Bepth artesian flow encounteredft.	
perature of water 7/ Depth artesian flow encountered ft.	Work started Aug /8 1980 Completed Aug 2/180
(9) CONSTRUCTION:	Date well drilling machine moved off of well Aug 2/ 19
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:
Well sealed from land surface to $6-24$ ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief
Diameter of well bore below seal	[Signed Day 2/10 80
Number of sacks of cement used in well seal sacks	(Drilling Magning Operator)
To top through soul line pipe	Drilling Machine Operator's License No
	Water Well Contractor's Certification:
*	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes 🗌 No Plugs Size: location ft.	Name Signal Oke of July 1 Drilling
Did any strata contain unusable water? Yes No	(Person, firm ostcorporation) (Type or print)
Type of water? depth of strata	Address MA 1397 101
Method of sealing strata off	[Signed]
Was well gravel packed? [] Yes No Size of gravel:	[Signed] (Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 25 6. Date Quig 2/ 1985