

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

RECEIVED

MAR 5 1973

STATE ENGINEER

SALEM, OREGON

State Well No.

2N/32E-22

(1) OWNER:

Name Dale Holverson
Address 1225 NW Ingram
Pendleton, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☐
6" Diam. from 0 ft. to 19 ft. Gage
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.
" " " "

Bar test 304 gal./min. with 20 ft. drawdown after 1 hrs.

Artesian flow g.p.m.

Temperature of water 61° Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 19' ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water 0 lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? WET depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☐ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Umatilla Driller's well number
SE 1/4 SE 1/4 Section 22 T. 2N R. 32 E W. M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well. 271' - water

Depth at which water was first found (Particle) 19' ft.
Static level 300' ft. below land surface. Date 12-29-72
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing

Depth drilled ft. Depth of completed well 403 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
SOIL	0	2	—
caliche white	2	4	—
Basalt grey	4	52	—
" Red clay	52	133	—
" grey	133	159	—
Rock Red	159	162	—
Basalt grey	162	203	—
Rock clay Red	203	229	—
Basalt grey	229	307	300'
Rock Red	307	320	275
Basalt grey	320	403	300

Work started 12-26 19 72 Completed 1-2 19 73

Date well drilling machine moved off of well 1-3 19 73

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] Don Gilbre Date 2-28, 19 73
(Drilling Machine Operator)

Drilling Machine Operator's License No. 181

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name LARRY BURD Well Drilling
(Person, firm or corporation) (Type or print)

Address P.O. Box 417 Pendleton, Ore

[Signed] Larry Burd
(Water Well Contractor)

Contractor's License No. 544 Date 2-28, 19 73