NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORRECEIVED

STATE OF OREGON

(Please type or print)

(Do not write above this line) ATER RESOURGE BEINT No.

N	Q'	V	2	8	19) 7 2	te	Well	No	(2)	N.	10	C	٠	
						J-17									

of well completion. (Do not write ab	SALEM. OREGON	UMAT
(1) OWNER:	(10) LOCATION OF WELL:	
Name LIVANE SKRAVNSTAD	County Um ATIMA Driller's well nu	mber j
Address RT2 Roy 177	45(a) 45(a) 4 Section 20 T. 6N	•
Milton Free JATER - ORE.	Bearing and distance from section or subdivision	₹ ±.
(2) TYPE OF WORK (check):		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	"7 (7) ft.
Rotary Driven Domestic Mandustrial Municipal		urface. Date 1/1-18-77
Cable	Artesian pressure ————————————————————————————————————	# *
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well h	elow casing \$
Y Diam from O ft to 140 ft. Gage 250	Depth drilled) 7 ft. Depth of compl	eted well
ft. Gage	Formation: Describe color, texture, grain size a	and structure of materials;
"Diam. fromft. toft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	
Type of perforator used Taga	MATERIAL	From To SWL
Size of perforations in. by in.	TENSOIL & HARD DAM	0 0
Size of perforations 124 in. by 8 in. 22.0 perforations from 21 ft. to 130 ft.	TOPINI OF BROKEN CLAY LO WRALK!	10 60 3
perforations fromft. toft.	med Block sand or small oravel	60 65
perforations from ft. to ft.	SMAIL GRADEL & COLLEGE SAND	65. 70
(A) CODEFIC.	(CHUING)	70
(7) SCREENS: Well screen installed? Yes No	med GRADEL - (clean)	70 76 70
Manufacturer's Name	Small to mad quaus & med	76,90
Type Model No. Diam. Slot size Set from ft. to ft.	Black SAND	190
Diam. Slot size Set from ft. to ft.	Sm gravel or Bround clay	90 100
	COMENT CIRAUEL XFOND SAND	132 120
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	(CALANG)	116 120
Was a pump test made? Yes No If yes, by whom?	med gravel or course sand	120 140 40
ld: 250 gal./min. with 100ft. drawdown after 3 hrs.	SMALL TO MAD GRAVE	140
" "	(CleAN)	160
" " "	med gravel or Brown clay	NO 170
Bailer test gal./min. with — ft. drawdown after — hrs.	SMALL GRAVEL OF BROWN Clay	170 175
Artesian flow g.p.m.		-5
apperature of water 5 Depth artesian flow encountered ft.	Work started / C-27 19 77 Complete	ed 11 - 1 8 1977
(A) CONCERNICATION	Date well drilling machine moved off of well	1/- 19 1977
(9) CONSTRUCTION:	Drilling Machine Operator's Certification:	
Well seal-Material used BENTONITE or Public Clay	This well was constructed under my	direct supervision.
Well sealed from land surface to	Materials used and information reported best knowledge and belief.	above are true to my
Diameter of well bore to bottom of seal		Date 1/-18, 1977
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	0856
Brand name of bentonite NATIBERAL	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	*This well was drilled under my jurisditrue to the best of my knowledge and bel	iction and this report is
Was a drive shoe used? Yes 🗆 No Plugs Size: location ft.	Marie True D	RILLING
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 131 2 180x 140 13	mit ore
Method of sealing strata off	[Signed] Lowel N. Mark	eth .
Was well gravel packed? ☐ Yes ☑ No Size of gravel:	(Water Well Contr	. /
Gravel placed from ft. to ft.	Contractor's License No. 265 Date	VOY 23 , 1977