File Original and First Copy with the STATE ENGINEER, SALEM, OREGON STATE ENGINEERWATER WELL REPORT

`		
G	1.0	-52

State Well No.

2N/32-27N

SALEM, OLEGOR			
(1) OWNER: Name STANLEY G WALLULIS	(11) WELL TESTS: Drawdown is amount we lowered below static level.  Was a pump test made? Yes No If yes, by whom?	ater level is	
Address 28 SB Byers ave.	Yield: 300 gal./min. with 130 ft. drawdown	after 8 hrs.	
Pendleton, Oregon	" 250 " 95 "	6 "	
	<u> </u>	۳ .	
(2) LOCATION OF WELL:	Bailer test gal./min. with ft. drawdown	after hrs.	
County Umatilla. Owner's number, if any W-W#/ 5W 1/4 of SW1/4 Section 27 T. 2 N R. 32 E. W.M.	Artesian flow 5 g.p.m. Date 3/29/	<u>′60</u>	
	Temperature of water 62 Was a chemical analysis made	ie? 🗌 Yes 🖫 No	
Bearing and distance from section or subdivision corner  N 67°32′30″E a 0':579NCE 0F	(10) XXXXI I T.O.C.	8	
1416.08 feet from S.W COR OF	(12) WELL LOG: Diameter of well  Depth drilled 155 ft. Depth of completed we	<u>O</u> inches.	
SECTION 27, TWW 2N, R32EW.M	Formation: Describe by color, character, size of material show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each ch	ie material in each	
NA.			
	MATERIAL	FROM TO	
(3) TYPE OF WORK (check):	Soil	0 8	
New Well Deepening Reconditioning Abandon	Gravel Grant Grant	8 13	
If abandonment, describe material and procedure in Item 11.	Cement gravel	13 18	
PROPOSED USE (check): (5) TYPE OF WELL:	Soil, gravel & clay	18 27	
(-,	Hardpan	27 40	
Cable X Jetted	Broken brown basalt	40 47	
Irrigation  Test Well Other Dug Bored	Brown basalt	47 60	
(6) CASING INSTALLED: Threaded □ Welded 🛚	Broken brown basalt	60 62	
"Diam. fromft. to	Grey basalt	62 96	
8 "Diam from 0 ft to 49 ft Gage Standa	nd	96 115	
" Diam. from ft. to ft. Gage	270112 3000-0	115 143	
Dian. 11011	Black basalt (WATER BEARING)	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	
(7) PERFORATIONS: Perforated?   Yes X No	Hard grey basalt	153 155	
Type of perforator used	-	100 100	
SIZE of perforations in. by in.			
perforations from ft. to ft.	1		
perforations from ft, to f	I :		
perforations from ft. to f			
perforations from	· •		
perforations from ft. to f			
(8) SCREENS: Well screen installed ☐ Yes 🖾 No			
Manufacturer's Name			
Type Model No			
Slot size Set from ft. to ft.	1		
am Slot size Set from ft, to ft	- / / / - ·	29/60 19	
(a) CONCERTIONON.	(10) DYIMD.		
(9) CONSTRUCTION:	(13) PUMP:		
Was well gravel packed? Yes X No Size of gravel:	Manufacturer's Name		
Gravel placed fromft. to	Type:	1.P	
Material used in seal— Comented bottom to top	_ Well Driller's Statement:		
Did any strata contain unusable water? 🗌 Yes 🏋 No	This well was drilled under my jurisdiction a	nd this report is	
Type of water? Depth of strata	true to the best of my knowledge and belief.		
Method of sealing strata off	TARE D K SMITH	•	
	NAME DK SMITH (Person, firm, or corporation) (Ty	pe or print)	
(10) WATER LEVELS:	Address ROUTE 3 WALLA WALLA WASHINGTON		
Static level 5 ft. below land surface Date  Artesian pressure Flower DM ibs per square inch Date 3/29/60	-		
Artesian pressure FlowsGPM lbs. per square inch Date 5/25/00	Driller's well number		
Log Accepted by:	[Signed] Spolmith		
Stanley Hall In Sail 28 106	(Well Driller)		
[Signed] Stanley Malledy Date agril 28, 19.60	License No. 204 Date 4/25/	60 19	
	<i>( ( .</i>		