NOTICE TO WATER WELL CONTRACTOR The original and first copy UM of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

STATE OF OREGON (Please type or print)

MAR 25 1976 State Well No. (Do not write above this paint RESOURCES Stole Permit No. ...

(1) OWNER:	(10) LOCATION OF WELL:		
Name GERALD WYLEND	County UneT/LLA Driller's well number 76-13		
Address RT 2 Box 83	Sw 4 Sw 4 Section 34 T. 2 N R. 32 E W.M.		
PENDLETON ORP	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Lot 4 west 3/De of Rodo		
New Well	FIELD CREST DIV		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 240 ft.		
Rotary Driven Domestic Industrial Municipal	Static level /47 ft. below land sur	face. Date 3-2/-7	
Bored Irrigation Test Well Other	Artesian pressure lbs. per square	inch. Date	
(5) CASING INSTALLED: Threaded Welded For the Gage 230	(12) WELL LOG: Diameter of well below casing 8"		
6 " Diam. from 1 1/2 ft. to 3/2 ft. Gage 230	Depth drilled 375 ft. Depth of completed well 375 ft.		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and		
(6) PERFORATIONS: Perforated? [] Yes [I] No.	and show thickness and nature of each stratum with at least one entry for each change of formatio position of Static Water Level and indicate princip	n. Report each change in	
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	5014	8 3	
perforations fromft. toft.	l	3 //	
perforations from ft. to ft.		1 220	
perforations from ft. to ft.	BESELT BROWN BRK	220 340	
(7) SCREENS: Well screen installed? \(\sigma\) ves \(\frac{1}{2}\) \(\text{No.}\)	n Rep 3	140 345	
(7) SCREENS: Well screen installed? ☐ Yes ② No Manufacturer's Name	11 BROWN	345 375	
Type Model No.			
Diam. Slot size Set from ft. to ft.	1 1 1 1 2 1 2 1 2 1 2 1		
Diam. Slot size Set from ft. to ft.	TO 8" CRSING	D AT TOP	
	70 8 223756		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	8" hole was DRILLE	D TO 375	
Was a test made? Yes Yo If yes, by whom?		Be 507	
gal./min. with 178 ft. drawdown after / hrs.	Behow 325'		
" " "			
" " " "		e Pushen	
Bailer test gal./min. with ft. drawdown after hrs.	POWN TO 375'		
exessian flow g.p.m.	• • • • • • • • • • • • • • • • • • • •		
Depth artesian flow encountered ft.	Work started 3-10 1976 Completed	7 - 9 47/	
(9) CONSTRUCTION:	Work started 3-10 1976 Completed 3-22 1976 Date well drilling machine moved off of well 3-22 1976		
Dandi- LA	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my direct supervision.		
Well sealed from land surface toft. Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my		
Diameter of well bore below seal in.	best knowledge and belief.		
Number of sacks of cement used in well seal/ 2 sacks	[Signed] Lang Burd Date 933, 1976		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 933		
Brand name of bentonite	Water Wall Contractorio Contractorio		
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name LORRY BURD WELL DRILLIU		
Did any strata contain unusable water? Yes 1 No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address P.O. Box 417 Probleton		
Method of sealing strata off	[Signed] Lung Burd		
Vas well gravel packed? Yes 4 No Size of gravel:	(Water Well Contractor)		
ravel placed from ft. to ft.	Contractor's License No. 544 Date 3-22, 1976		