NOTICE TO WATER WELL CONTINUE The original and first copy of this report are to be filed with the SEP7 - 1972 STATE OF OREGON

State Well No.

STATE ENGINEER, SALEM, OREGON 91816 ENGINE EXECUTION within 30 days from the date of well completion. SALEM OF: (199 not write above this line)

State Permit No.

-	
(1) OWNER:	(10) LOCATION OF WELL:
Name Charles livres	County /malilla Driller's well number
Address 1002 N.W. 47 H Xp1 A	14 14 Section 34 T. 27 R. 32 E. W.M.
Penderson, Oregon 47801	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 66
Rotary 🖄 Driven 🗌 Domestic 🔀 Industrial 🗌 Municipal 🖂	Static level 50 ft. below land surface. Date 8/29/77
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	
CASING INSTALLED: Threaded □ Welded A	(12) WELL LOG: Diameter of well below casing 6"
"Diam. from ft. to ft. Gage	Depth drilled 275 ft. Depth of completed well 275 ft.
	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Tyes 12 No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsvil 04
perforations from ft. to ft.	Shavel 4 15
perforations from ft. to ft.	Rock, med. black 15 63
perforations from ft. to ft.	Kick red - 63 66 W.B.
(7) SCREENS: Well screen installed? West No.	Tack, Sight Grown 66 73
Manufacturer's Name	Rock, med. black 73 94
Type Model No.	Rock, ked + green claystone 94 103 Rock, med., black 103 126
Diam Slot size Set from ft. to ft.	Basalt 126 1/5
Diam, Slot size Set from ft. to ft.	Rock med. black 165 172
(8) WELL TESTS: Drawdown is amount water level is	Rock Hack & rud hack 172 174
lowered below static level	Rock hed 174 181 W13.
Was a pump test made? Tyes M No If yes, by whom?	Rock, med., black 181 197 W.B.
Yield: gal./min. with ft. drawdown after hrs.	- Pasalt 197 201
" " "	Dasalt, med. glag 201 242
The state of the s	Basalt, aran 273 273 W.B.
Bailer test 35 gal./min. with 2/3 ft. drawdown after / hrs.	- Dazett, 4704 213 213
Artesian flow g.p.m.	
Temperature of water Depth artesian flow encountered ft.	Work started 8-25 1972 Completed 8-29 1972
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-29 1972
Well seal—Material used Clement	Drilling Machine Operator's Certification:
Well sealed from land surface to 20 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Date 8-36, 19.72
Number of sacks of cement used in well seal sacks	
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Was a drive shoe used? XYes ☐ No Plugs Size: location ft. Did any strata contain unusable water? ☐ Yes ☒ No	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
	(Person, firm or corporation) (Type or print) Address 900 HERMISTON AVE. HERMISTON ORE
Type of water? depth of strata Method of sealing strata off	Audress 100 AL STORY AVE, MERMISTIMORE
	[Signed] July Houghen
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 65 Date 8-30 , 19.72