NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT

## STATE OF OREGON

(Please type or print)

(Do not write above this line)

	_	4
UMA	TSate	Well No. 21/32E-356 b
720	1	Permit No.
127	State	Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name KOBEL MONTEE	County (1) Day T) (4)		
Address GII NW 3	NWW Shill section 25 m All - 27%		
(2) TYPE OF WORK (1)	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	or season correct		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Ifem 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 30		
Rotary Driven Domestic Industrial Municipal D	Static level 149 ft. below land surface. Date 4-18-86		
Dag   Bored   Irrigation   Test Well   Other	Artesian pressure lbs. per square inch. Date		
(5) CASING INSTALLED: Threaded  Welded	(12) WELL LOG: Diameter of well below casing 8		
0" Diam. from +2 ft. to 18 ft. Gage 1250	Depth drilled ft Donth of complete vi		
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;		
	and show inckness and nature of each stratum and aquifor nanotucted		
(6) PERFORATIONS: Perforated?   Yes   No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	SOIL 6 6		
perforations from ft. toft.	gequel 68		
perforations from ft. to ft.	Black Baralt 8 90		
perforations from ft. to ft.	B/Ack + Brown Book 75 85		
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Black Basalt PS 965		
Manufacturer's Name	Brack + Brown Bosah 3/65 385		
Type Model No	Black & Red Bosalt 385 395 160		
Diam. Slot size ft. to ft.	2/1/2		
Diam. Slot size Set from ft. to ft.	Black Boyall 450 450		
(8) WELL TESTS: Drawdown is amount water level is	Wachtled Bosalt yellow Tak 480 490 H20		
Alk Tout lowered below static level	Black Bosalt 490 495		
a pump test made? Tyes GNO If yes, by whom? Uriler	251 FIVED		
Yield: 300 gal./min. with 25/ ft. drawdown after hrs.			
the supplied that the supplied the supplied the supplied to th			
11 11 11 11 11 11 11 11 11 11 11 11 11	WATER RESOURCES DEPT -		
er test gal./min. with ft. drawdown after hrs.	SALEM. OREGON		
Artesian flow g.p.m.	2		
Temperature of water Depth artesian flow encounteredft.	Work started 4- 18 19 80 Completed 5-18 19 80		
(9) CONSTRUCTION;	Date well drilling machine moved off of well 5-18 1980		
Well seal-Material used OUTLAND CENCY	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my direct supervision		
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below seal	[Signed] 7 2 10 10 80		
Number of sacks of cement used in well seal sacks sacks sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No. 1345		
	Water Well Contractor's Certification:		
Vas a drive shoe used? T Vec T	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Vas a drive shoe used?  Yes  To Flugs Size: location ft.	Name LAD How Well Dockers		
7.00 05	(Person, firm or corporation) (Type or print)		
depth of strata  lethod of sealing strata off	Address Kt (Box) 4 ( ot his Dia 92%)		
	[Signed]		
The state of the s	(Water Well Contractor)		
ravel placed from ft. to ft.	Contractor's License No. 739 Date 5-18, 1980		
(USE ADDITIONAL SHEETS IF NECESSARV)			