NOTICE TO WATER WELL CONTRACTOR
The original and first copy

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9310 756 within 30 days from the date of well completion.

WATER WELL REPORECEIVED

STATE OF OREGON

JAN 31 1974 State Well No. 21

1 No. 2N 33E-2

(Please type or print)

(Do not write above this line STATE ENGINEEr ate Permit No. ....

SALEM OREGON

(1) OWNER:	(10) LOCATION OF WELL:		
Name Jim Phelps	County Umatilla Driller's well number		
Address 3344 S. W. Kirk Pendleton, Ore. 9780I	½ ½ Section 2 T. 2N	R. 33 W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	e <b>ll.</b>	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 47	ft.	
Rotary $\stackrel{Z}{=}$ Driven $\square$ Domestic $\stackrel{X}{\square}$ Industrial $\square$ Municipal $\square$	Static level 8 ft. below land st	urface. Date I-29-74	
Dug	Artesian pressure Ibs. per square	- L	
CASING INSTALLED: Threaded □ Welded ☑  6  " Diam. from 0  ft. to 23  ft. Gage	(12) WELL LOG: Diameter of well below casing 6  Depth drilled ft. Depth of completed well ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,		
DEDECOR A MYONIC.	with at least one entry for each change of format position of Static Water Level and indicate princ	ion. Report each change in	
		From To SWL	
Type of perforator used	surface sandy soil		
Size of perforations in, by in,	Gravel	0 <u>13</u> 13 18	
perforations from	rock black coarse	18 47	
perforations fromft. toft.	rock red soft	47 6I 8	
perforations from ft. to ft.	rock black hard	6I I05 8	
(7) SCREENS: Well screen installed? ☐ Yes ₩ No			
Manufacturer's Name			
Type Model No	A		
Diam Slot size Set from ft. to ft.	Man.		
Diam, Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
aur " " "	,		
GO 25 Gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.  erature of water Depth artesian flow encountered	Work started I-25 19 74 Complete	ed I-29 19 74	
(0) CONSTRUCTION.		F30 19 74	
(9) CONSTRUCTION: cement	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my	direct supervision.	
well sealed from land surface to	Materials used and information reported best knowledge and belief.	above are true to my	
Diameter of well bore to bottom of seal	reservation of the second seco	Data T=30 10.74	
Number of sacks of cement used in well sealsacks	[Signed] (Orilling Machine Operator)	300	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.		
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of waterlbs./100 gals.	This well was drilled under my jurisdi		
Was a drive shoe used? ★ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.		
Did any strata contain unusable water? 🗌 Yes 💆 No	Name (Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	AddressR. R. 2 Box 309-C Hormist	ton, Ore. 97838	
Method of sealing strata off	Some Alling	1	
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] J. 1. Co. (Water Well Contr.		
Gravel placed from ft. to ft.	Contractor's License No Date	<del>-</del> 30 74	
_		,	