NOTICE TO WATER WELL CONTRACTOR

SALEM, OREGON 97310

within 30 days from the date

The original and first copy of this report are to be filed with the STATE OF OREGON JUL 16 1979 Please type or print) WATER RESOURCES DEPARTMENT,

State	Well	No.	2 N /33E	-3ac
State	Well	No.	2 N/33E	-3ac

State Permit No. ....

of well completion. WATER RESOURCES no EPF ab	ove mis me,		
1) OWNER:	(10) LOCATION OF WELL:		
Name Burl Becker	County Umatilla Driller's well nu	mber	
Address P.O. Box 83	- obs	R. 33E W.M.	
Pendleton, Oregon 97801	Bearing and distance from section or subdivision		
2) TYPE OF WORK (check):	Bearing and distance from section of subdivision	III COINCI	
New Well ☑ Deepening □ Reconditioning □ Abandon □			
f abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed we	ell.	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 16	<del>/</del>	
totary Driven Domestic Industrial Municipal	Static level 70 ft. below land st	urface. Date 7-12-79	
Cable	Artesian pressure lbs. per square	e inch. Date	
CASING INSTALLED: Threaded   Welded   8 " Diam. from +2 ft. to 18 ft. Gage • 250	(12) WELL LOG: Diameter of well be Depth drilled 410 ft. Depth of complete	elow casing 8 eted well 410 ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
" Diam. from ft. to ft. Gage	and show thickness and nature of each strature with at least one entry for each change of format		
PERFORATIONS: Perforated?   Yes   Ye	position of Static Water Level and indicate prin		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Soil	0 6	
perforations from ft. to ft.	Gravel	6 12	
perforations fromft. toft.	Black Basalt	12 110	
perforations from ft. to ft.	Blak Basalt&Green Talc	110 120	
	Blak Basalt	120 169	
(7) SCREENS: Well screen installed?   Yes   No	Black Basalt& Green Talc	169 190 70	
Manufacturer's Name	Blak Basalt	190 222	
Type Model No	Black Basalt & Green Talc	222 31 5/	
Diam Slot size Set from ft. to ft.	Black Basalt	31 5 372	
Diam Slot size Set from ft. to ft.	Red & Black Basalt	372 380	
(8) WELL TESTS: Air Tested  Drawdown is amount water level is lowered below static level	Black Basalt	380 410	
Was a pump test made?  Yes No If yes, by whom?			
Yield: 130 gal./min. with 106 ft. drawdown after 1 hrs.			
" "			
n n n n	-		
Bailer test gal./min. with ft. drawdown after hrs.			
Artesian flow g.p.m.			
perature of water 64 Depth artesian flow encountered ft.	Work started 7-9 19-79 Complete	ed 7-12 1979	
(A) CONCERNICATION	Date well drilling machine moved off of well	7-12 1979	
(9) CONSTRUCTION:	Dailling Machine Operator's Contification:		
Well seal—Material used Portland Dement  Well sealed from land surface to 18 ft.  Diameter of well bore to bottom of seal 12 in.	Drilling Machine Operator's Certification:  This well was constructed under my Materials used and information reported best knowledge and belief.	direct supervision.	
Diameter of well bore below seal	[Signed] Frida How	Date 7-12 , 1979	
Number of sacks of cement used in well seal 10 sacks	(Drilling Machine Operator)	1 21 5	
How was cement grout placed?pumped	Drilling Machine Operator's License No.	1242	
	Water Well Contractor's Certification:		
	This well was drilled under my jurisd true to the best of my knowledge and be	iction and this report is	
Was a drive shoe used? ☐ Yes Plugs Size: location ft.	Todd Hom Woll Drilling		
Did any strata contain unusable water?   Yes No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address Rt.1 Box 14, Pilot	Rock, Øre. 9786	
Method of sealing strata off	[Signed] Rold How		
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No739 Date	7 <u>–12</u> , 19. 7	