NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

## WATER WELL REPORT CEIVED

STATE OF OREGON JUL 3 1 1974 State Well No. 2N/33E-3cc

(Please type of print) STATE ENGINEER State Permit No.

(Do not write above this line) LEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name JEAN WALKER	County UMATILLA Driller's well number 75
Address Penpheron GRE.	SW 1/4 SW 1/4 Section 3 # T. 2N R. 33 E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 74 ft.
Rotary Driven Domestic Industrial Municipal D	Static level /6 ft. below land surface. Date 7-11-74
Cable	Artesian pressure Ibs. per square inch. Date
CASING INSTALLED: Threaded   Welded   W	(12) WELL LOG: Diameter of well below casing S  Depth drilled 203 ft. Depth of completed well 205 ft.  Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	GRAVEL 0 /2
perforations from ft. to ft.	CLE1 12 20
perforations from ft. to ft.	BASALT BLACK MED 20 74
perforations from ft. to ft.	1. 11 SOFT 74 102 420
(7) SCREENS: Well screen installed? ☐ Yes 🖟 No	Hard 102 108
(7) SCREENS: Well screen installed? ☐ Yes 🖟 No Manufacturer's Name	11 GREY HORD 108 205
Type Model No	
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
Diditi Siot size	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	***
" " "	
" " "	
HIR Jaller test 30 gal./min. with ft. drawdown after hrs.	
	BSer.
Artesian flow g.p.m.  perature of water 36 Depth artesian flow encountered	Work started 7 - 4 19 7 4 Completed 10-11 1974
	Date well drilling machine moved off of well 19 74
(9) CONSTRUCTION:	Dulling Machine Operator's Contitiontions
Well seal—Material used PORTLOND COMENT  Well sealed from land surface to 26 ft.  Diameter of well bore to bottom of seal 12 in.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Java Bud Date 7-/1, 1974.
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No. 933
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Literise No.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used?   Yes   You Plugs Size: location ft.	Name Le Rey BURD Well DRILLING (Person, firm or corporation) (Type or print)
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address P O BOX 417 Pendlaton
Method of sealing strata off	[Signed] Jany Bund
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 544 Date 10-11 , 19.74