NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT MAR 3

1975 STATE OF OREGON

State Well No. 2N/33E-8 ca

(Please type or print) STATE ENGINEER State Permit No.
(Do not write above this MALEM, OREGON

STATE ENGINEER, SALEM, OREGON 97310 (15) within 30 days from the date of well completion.

(1) OWNER:	(10) LOCATION OF WELL:	٠	
Name ROBERT FETSCH	County UM27/LLA Driller's well nu	mber 75-5	
Address RT 1, BGY 134 J 1	NE 454 4 Section 8 T. 2N		
PENDLETON ORE	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	72 × 60 T 2220		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WARRED I EXTEL. Completed w		
	(11) WATER LEVEL: Completed well. Death at which water was first found 450, ft.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was the real way		
Rotary Driven Domestic Industrial Municipal Domestic Industrial Municipal	Static level 27' ft. below land s	ourface. Date 2-/9-73	
Dug	Artesian pressurelbs. per squar	e inch. Date	
ALCONO STAGE AT THE			
(a) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing		
"Diam. from XISTING ft. Gage	Depth drilled 145 ft. Depth of completed well 470 ft.		
ft. Gage	Formation: Describe color, texture, grain size a	and structure of materials;	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes Yes	position of Static Water Level and indicate prin	cipal water-bearing strata.	
	MATERIAL	From To SWL	
Type of perforator used	A CONTRACTOR OF THE PARTY OF TH	325 360	
Size of perforations in. by in.	BASALT BLECH	360 450	
perforations fromft. toft.	11 Rep	450 470	
perforations from ft. to ft.	TO THE PARTY OF TH	175 170	
perforations from ft. to ft.			
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name	in the second se		
Type Model No			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☐ No If yes, by whom?			
gal./min. with 3/7 ft. drawdown after hrs.	A STATE OF THE STA		
	- 0,0		
	The second of th		
" 50 " 103 " "	for a second of the second of		
Bailer test gal./min. with ft. drawdown after hrs.			
Ariesian flow g.p.m.			
inperature of water 66 Depth artesian flow encountered ft.	Work started 2-/7 1975 Complet	ed 2 - 20	
(A) CONCERNICETON	Date well drilling machine moved off of well	2-20 1975	
(9) CONSTRUCTION:	Drilling Machine Operator's Certification	•	
Well seal-Material used EXISTING	This well was constructed under my	direct supervision.	
Well sealed from land surface to ft.	Materials used and information reported	above are true to my	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	Date -2-20 19 75	
Diameter of well bore below seal in.	(Drilling Machine Operator)		
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.	933	
Number of sacks of bentonite used in well seal sacks	2.1		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is		
of waterlbs./100 gals. Was a drive shoe used? Yes Ao Plugs Size: location ft.	true to the best of my knowledge and belief.		
	Name Larry Burd Well DRILLING (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes No	DO ROY AID PONDLOTON		
Type of water? depth of strata	Address O D T		
Method of sealing strata off	[Signed] Jony Buch	manaran	
Was well gravel packed? Tyes WNo Size of gravel:	(Water Well Cont		
Gravel placed from ft. to ft.	Contractor's License No. 574 Date	<u>4749</u> , 19.7.3	