NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT STATE OF OREGON EC 2 6 1974

(Please type or prinGTATE ENGINEER

(Do not write above this SIADEM, OREGOII (-6907

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:
Name Bill Weett	County Umatilla Driller's well number
Address adams, Oregon 97810	NE 14 NW14 Section 8 T. 271, R. 33E, W.M.
Address of days, grayore	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well Deepening □ Reconditioning □ Abandon □	
If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found // ft.
Rotary S. Driven Domestic Industrial Municipal Domestic	Static level 150 ft. below land surface. Date 12/20/14
Dug ☐ Bored ☐ Irrigation ☑ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded □ Welded ♥ 8 "Diam from 0 ft to 10 ft Gage 12.50 # Gage 12.50 "Diam from ft to 10 ft Gage 10	(12) WELL LOG: Diameter of well below casing 8" Depth drilled 4/0 ft. Depth of completed well 4/0 ft. Formation: Describe color, texture, grain size and structure of materials;
PERFORATIONS: Perforated? Yes No.	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Topsie 0 2
perforations from ft. toft.	Shavel + boulders 2 11
perforations from ft. to ft.	Basalr, black 11 16
perforations fromft. toft.	Basact, hard, gruy 16 67
	Rock dark brown blue layating 67 71 W.B.
(7) SCREENS: Well screen installed? ☐ Yes ▼ No	Rock med. black 11 127
Manufacturer's Name	Rock light frown 127 132
Type Model No	Rock, black 132 138
Diam. Slot size Set from ft. to ft.	Basalt, gray 138 153
Diam. Slot size Set from ft. to ft.	Rrck, black+ often clayother 153 185 W.B.
(8) WELL TESTS: Drawdown is amount water level is	Rock, light brown 185 210
lowered below static level	Rock, Thed black 210 294
Was a pump test made? ☐ Yes 🖫 No If yes, by whom?	Dosalt, Kud, Gray 294 306
Yield: gal./min. with ft. drawdown after hrs.	Basell hard gran 312 358
" "	Rock hed alay hown 358 375 W.B.
" "	Burely 91 and 375 382
Bailer test 300 gal./min. with 2-50 ft. drawdown after 1 hrs.	Rock, light brown 382 410 WB
Artesian flow g.p.m.	The second secon
perature of water Depth artesian flow encountered ft.	Work started /2-17 1974 Completed /2-20 1974
	Date well drilling machine moved off of well /2-21 1974
(9) CONSTRUCTION:	
Well seal-Material used Cenunt	Drilling Machine Operator's Certification:
Well sealed from land surface to 72 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.
Diameter of well bore below seal in.	[Signed] Lames Tallak Date 12-23, 1974
Number of sacks of cement used in well seal 14 sacks	Drilling Machine Operator's License No. 6.5
Number of sacks of bentonite used in well seal sacks	Diffing Machine Operator & License 170,xx.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water	true to the best of my knowledge and belief.
Was a drive shoe used? ✓ Yes No Plugs Size: location ft.	Name TROY GRIFFIN (Person, firm or corporation) (Type or print)
Did any strata contain unusable water? [8] Yes [] No	1 · · · · · · · · · · · · · · · · · · ·
Type of water? Surface depth of strata !	Address 900 HERMISTON AVE. HERMISTON OF
Method of sealing strata off (livery Not a array	[Signed] Troy Hruskin,
Was well gravel packed? Yes No Size of gravel:	(Water Well Sontractor)
Crown land from 4t to 5t	Contractor's License No 65 Date 17-23 1974