NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

Unio 1049

STATE OF OREGON

11981 State Well No. 1

(Please type or print)

(Do not write above that RESOURCES SEEP ermit No.

SALEM, OREGON

(1) OWNER:	(10) LOCATION OF WELL:			
Name BOB SERMONS	County UNION Driller's well number			
Address 11TA STREET	NE 14 NR 14 Section 16 T.35	R. 38	E	W.M.
LE GRENDE ORP 97450	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL. Completed an			
	(11) WATER LEVEL: Completed well.			
	Depth at which water was first found 62 ft.			
Rotary Driven Domestic Industrial Municipal Cable Deficient	Static level 6 ft. below land s	urface. D	ate /0	<u>~13/80</u>
Dug	Artesian pressure lbs. per squar	e inch. D	ate	
/2 "Diam. from t / tt. to /9 tt. Gage • 250 // Diam. from t / tt. to -225 tt. Gage • 250 "Diam. from tt. to tt. to ft. Gage • 250 "Diam. from ft. to ft. Gage	(12) WELL LOG: Diameter of well below casing Depth drilled 243 ft. Depth of completed well 243 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.			
(v) PERFORATIONS: Perforated? Yes No.		r		
Type of perforator used	MATERIAL	From	To	SWL
Size of perforations in. by in.	SolL	0	4	
perforations from ft. to ft.	SEND		62	<u> H20</u>
perforations from	GAZVEL 62	7-7-	90	
perforations from ft. to ft.	SOND	1	96	
(7) SCREENS: Well'screen installed? Yes No	GREVEL	1	104	HEO
Manufacturer's Name	Saun Stone	, , ,	132	11.0
Type JOHNSON Model No.	CRIVEL		• •	H20
Diam /0"7(1\siot size : 020 Set from 242 ft. to 222 ft.	SEND GREVEL & CLO'		2/5	
Diam. Slot size Set from ft. to ft.	Sand		220	H20
Diam. Slot size Set from It. to It.	SEND			ALU
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	SILTSTONE	240	243	
	NCO TO TO	h		
Was a pump test made? Lifes □ No If yes, by whom? DRILLEN	<u> </u>			
y'd: 720 gal/min. with 7/ ft. drawdown after / hrs.	MAY 1 0 1001			
" "	— MAY 1 8 1981			
n " " "	WATER RESOURCES DEF	T		
Bailer test gal./min. with ft. drawdown after hrs.	SALEM, OREGON			
Artesian flow g.p.m.				
aperature of water 52° Depth artesian flow encountered ft.	Work started /0~/ 1960 Complete	ed //	0-13	1980
(A) CONSTRUCTION.	Date well drilling machine moved off of well	10	7-13	19 80
(9) CONSTRUCTION: Well seal—Material used PR7 LOND COMENT	Drilling Machine Operator's Certification:			
Well seal—Material used	This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Date 14, 1987. Drilling Machine Operator) Drilling Machine Operator's License No. 933.			
			•	
10" Stoe usen	Water Well Contractor's Certification:	,	× 4	
NO 12" " "	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Jang Burd Wall Drilling Trees or print)			
Did any strata contain unusable water? Yes No	Address 5.543 Sw Danglas ;			
Type of water? depth of strata	Autress	from Trade		1 <i>1</i>
Method of sealing strata off	[Signed] (Water Well Contractor)			
Was well gravel packed? Yes No Size of gravel:	• • • • • • • • • • • • • • • • • • • •		L	On
Gravel placed from ft. to ft.	Contractor's License No. 5.44 Date		1	., 19. 5 .0