NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED

(Please type or print) (Do not write above this line)

this line)	R RESOL	JRCES	DE	PT.			,
rint)	JUN 4	1976	State	Permit	No.	35/394	

OWNER:	(10) LOCATION OF WELL:	
D T Double	County Union Priller's well nu	mber 23 ez
ame B. L. Davis ddress Adams, Oregon 97810	NE 14 NW 14 Section / 22 T. 3S	R. 39E. W.M.
duress Madazo (01 08 01)	Bearing and distance from section or subdivision	-
2) TYPE OF WORK (check):	Dearing and absence from booken of bases, and	
Abandon 🗆		
ew Well Deepening Reconditioning Abandon Season Reconditioning Rec	(11) THE MIND I HAVET . Completed	
	(11) WATER LEVEL: Completed we	
3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	25 <u>ft.</u>
otary 🙎 Driven 🗋 Domestic 🗌 Industrial 🗎 Municipal 🗍	Static level 25 ft. below land s	urface. Date <u>5/10/76</u>
able	Artesian pressure lbs. per square	e inch. Date
		26
CASING INSTALLED: Threaded □ Welded ☑	(12) WELL LOG: Diameter of well b	elow casing 26
16 " Diam. from ±1 ft. to 274 ft. Gage •250	Depth drilled 292 ft. Depth of comple	eted well 292 ft.
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a	nd structure of materials;
" Diam. from ft. to ft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format	n and aquifer penetrated, ion. Report each change in
PERFORATIONS: Perforated? T Yes No.	position of Static Water Level and indicate prin	cipal water-bearing strata
·	MATERIAL	From To SWL
ype of perforator used <u>Machine</u>	Top soil	0 8
ize of periorations	Clay brown	8 28
5712 perforations from 127 ft. to 246 ft.	Clay & sand layers	28 51
perforations from ft. to ft.	Clay blue	51 57
perforations from	Clay & sand layers	57 93
7) SCREENS: Well screen installed? Yes No	Clay green	93 103
fanufacturer's Name	Clay blue	103 113
Type	Clay brown	113 119
Diam. Slot size Set from ft. to ft.	Clay green	119 127
Diam. Slot size Set from ft. to ft.	Sand & clay layers	127 133
	Clay sandy & sand layers	133 153
8) WELL TESTS: Drawdown is amount water level is lowered below static level	Sand & clay layers	153 168
Was a pump test made? W Yes D No If yes, by whom?Courtright	Sand	168 173
3000	Sand & clay layers	173 186
	Clay & sandstone	186 198
	Sand	198 201
n " n "	Clay dark green	201 205
Bailer test gal./min. with ft. drawdown after hrs.	Sand & fine gravel	205 215
Artesian flow g.p.m.	Clay dark green	215 224
perature of water Depth artesian flow encountered ft.	Work started 5/8 1976 Complet	ed $5/10$ 19 7
	Date well drilling machine moved off of well	5/10 ₁₉ 70
(9) CONSTRUCTION:	D 131 35 1 in Constant Contidiontion	
Well seal—Material used Cement	Drilling Machine Operator's Certification: This well was constructed under my	
Well sealed from land surface toft.	Materials used and information reported	above are true to my
Diameter of well bore to bottom of seal26 in.	best knowledge and belief.	6/2 17
Diameter of well bore below seal26 in.	[Signed](Drilling Machine Operator)	Date 6/2 , 19.70
Number of sacks of cement used in well seal50sacks	Drilling Machine Operator's License No.	755
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	4
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	iction and this report i
of water lbs./100 gals.	true to the best of my knowledge and be	lief.
Was a drive shoe used? 🗌 Yes 🙎 No Plugs Size: location ft.	Name Steve Moore	/Type as select
Did any strata contain unusable water? 🗌 Yes 🛣 No	(Person, firm or corporation) Address P. O. Drawer P. Moses	(Type or print) Lake, Wa. 98837
Type of water? depth of strata	Address 1. 0. Diawel F. noses	
Method of sealing strata off	[Signed] Steve Moore	
Was well gravel packed? No Size of gravel:1/8"-3/8"	(Water Well Cont	
Gravel placed from 18 ft. to 292 ft.	Contractor's License No628 Date	6/2 , 1979
Graver process from	RETS IF NECESSARY)	SP*45656-1

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

STATE OF OREGON

			Page 2
State	Well	No.	***************************************

STATE ENGINEER, SALEM, OREGON 97310 (Please type within 30 days from the date of well completion. (Do not write about the completion).	State Permit N	o		
	(10) LOCATION OF WELL:			
(1) OWNER:	County Union Driller's well number			
Name B. L. Davis	County Onition	R. 39E. W.M.		
Address Adams, Oregon 97810				
	Bearing and distance from section or subdivisi	on corner		
(2) TYPE OF WORK (check):				
New Well □ Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	rell.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.		
Rotary Driven Domestic Industrial Municipal	Static level ft. below land	surface. Date		
Cable	Artesian pressure lbs. per squar	re inch. Date		
CACING INCMALLED.	(19) WELL LOG:			
CASING INSTALLED: Threaded Welded		below casingleted well ft.		
" Diam. from ft. to ft. Gage	Depth drilled ft. Depth of comp			
	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forms position of Static Water Level and indicate prin	m and aquifer penetrated, ation. Report each change in		
PERFORATIONS: Perforated?	position of Static Water Level and indicate pro-			
/pe of perforator used	MATERIAL	From To SWL		
Size of perforations in. by in.	Clay gray	224 236		
perforations from ft. to ft.	Sand fine dark green	236 244		
perforations from	Clay green some brown	244 265		
perforations from ft. to ft.	Sandstone black	265 269		
periora sono 2 one	Clay gray soft	269 292		
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name				
Type				
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.		 		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level				
Was a pump test made? Yes No If yes, by whom?		 		
Yield: gal./min. with ft. drawdown after hrs.				
" " "		+		
" " "		+		
		+		
Bailer test gal./min. with ft. drawdown after hrs.		 		
Artesian flow g.p.m.	10 (3	eted 19		
perature of water Depth artesian flow encountered ft.	Work started 19 Complete Date well drilling machine moved off of well			
(9) CONSTRUCTION:				
Well seal—Material used	Drilling Machine Operator's Certification This well was constructed under m	ı. v direct supervision.		
Well sealed from land surface toft.	Materials used and information reported	d above are true to my		
Diameter of well bore to bottom of seal in.	best knowledge and belief.			
Diameter of well bore below seal in.	[Signed](Drilling Machine Operator)	Date, 19		
Number of sacks of cement used in well seal sacks				
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.			
Brand name of bentonite	Water Well Contractor's Certification:	1		
Number of pounds of bentonite per 100 gallons	This well was drilled under my juris	diction and this report is		
of water lbs./100 gals.	true to the best of my knowledge and b	elief.		
was a drive shoe used? ☐ Yes ☐ No Plugs Size: location ft.	1			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation)	(Type or print)		
7 47 - 4 - 4 - 4 - 4	Address			
1)pc 02 (42101)				
Method of sealing strata off	[Signed](Water Well Co	ntractor)		

Was well gravel packed? Yes No Size of gravel:

Gravel placed from ft. to ft.

Moore Drilling, Inc.

P. O. DRAWER P • MOSES LAKE, WASHINGTON 98837

Telephones: Moses Lake 765-8481 • Quincy 787-3793

August 4, 1976

RECEIVED

AUGO 1976 WATER RESOURCES DEPT. SALEM, CRECON

Water Resources Department 1178 Chemeketa Street NE Salem, Oregon 97310

Gentlemen:

On June 2, 1976, we sent you a water well report for B. L. Davis for a well drilled 292' and finished on May 10, 1976. The driller's well number and the legal description are in error. This should read driller's well number 3, and the legal description should read NW% of SW% Section 1, Township 3S, Range 39E.W.M. Please change your copy to agree with this information.

Also, will you please mail 25 Intent to Drill cards to P. O. Drawer P, Moses Lake, Wa. 98837.

Sincerely yours,

XX ...

Steve Moore

SM:eb

Enclosures