## NOTICE TO WATER WELL CONTROL C E IVE D The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGINANTE ENGINEER type or print) within 30 days from the date of well completion. SALEM OREGINA write above this line) C-459 St. C - 1813

State Well No. .

State Permit No. .....

(1) OWNER:	(11) LOCATION OF WELL:
Name MERTON TAYLOR	County UN / 0 N Driller's well number
Address 156 AND CITY, BRE.	14 5 £ 14 Section 4 T. 3 5 R. 3 9 E W.M.
	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	LOCATED ON SW CORNER OF - The
New Well Deepening Reconditioning Abandon	Above
If abandonment, describe material and procedure in Item 12.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing
Rotary Driven Domestic Industrial Municipal	Depth drilled 2 70 ft. Depth of completed well 255 ft.
Cable   Jetted     Domestic   Industrial   Maintage	
CASING INSTALLED: Threaded Welded Welded Down to Land St. to Land St. Gage 42.5	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.
" Diam. from ft. to ft. Gage	MATERIAL From To SWL
" Diam. from ft. to ft. Gage	SANDY TOPSOIL 0 18
PERFORATIONS: Perforated? Yes   No.	CLAY W/GRAYSAND 18 26
.ype of perforator used FACTORY PERF.	BROWN EANDY CLAY 24 88
	" " W/GRAVEL 58 99
Size of perforations 1/8" in. by 3 in.	BLUE SANDYCLAY W/ 99 112
3848 perforations from 13.5 ft. to 2.5.5 ft.	OCCASIONAL GRAVEL 1
perforations from ft. to ft.	BLUK MED. SAND 212-119
perforations from ft. to ft.	11 SANDY CLAYCHANG 119
perforations from	ING TOBROWN, OCC. GRAVEL 138
perforations from	MED-SAND, SOMEGRAVEL 138 159
(7) SCREENS: Well screen installed?   Yes No	MED. TO COARSE JAND, SUALL
Manufacturer's Name	GRAVEL 159 260
Type	SANDY BLUE CLAPU
Diam. Slot size Set from ft. to ft.	- GANEL 260 280
Diam. Slot size Set from ft. to ft.	
(8) WATER LEVEL: Completed well.	
Static level 14'6" ft. below land surface Date / 0/31/68	
sian pressure lbs. per square facts. Date	
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? 🗌 Yes 🙀 No If yes, by whom?	
'leid: 100 + gal./min. with 10 ft. drawdown after 4 hrs.	Work started OCT, 2 1968 Completed OCT, 30 1968
" "	Date well drilling machine moved off of well OCT. 31 1968
н н	Drilling Machine Operator's Certification:
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my direct supervision. Materials used and information reported above are true to my best
Artesian flow g.p.m. Date	knowledge and belief.
C _ A	[Signed] Defiling Machine Operator) Date 10/61, 19/8
Temperature of water 35 Was a chemical analysis made? ☐ Yes 2 No	(Drining Machine Operator)
(10) CONSTRUCTION:	Drilling Machine Operator's License No
Well seal-Material used CONCRETE	
Depth of seal	Water Well Contractor's Certification:
Diameter of well bore to bottom of sealin.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Were any loose strata cemented off? Yes No Depth Depth	NAME OHTS EllSWORTH
Was a drive shoe used? ☐ Yes ☒ No	(Person, firm or corporation) (Type or print)
Did any strata contain unusable water?   Tes No	Address PD. BOX 471 ISHNO 4TY DRISON
Type of water? depth of strate	OH COO 9T
Method of sealing strata off	[Signed] (M) ZWW MUM (Water Well Contractor)
Was well gravel packed? Yes No Size of gravel:	290 11/1 10
Summer of the state of the stat	Contractor's License No. 2 / 1 Date // / 19.5.5