NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the
STATE ENGINEER, SALEM 10, OREGON
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

State Permit No. .

	1			
(1) OWNER:	(11) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? If Yes No If yes, by whom?			
Name StANley WeishAAR-	- I		~	
Address of mand, OPC-	Yield: 2400 gal./min. with 90 ft. drawdown	after 2	k hrs.	
(2) LOCATION OF WELL:		- 64		
County Driller's well number	Bailer test gal./min. with ft. drawdown	aiter	hrs.	
14 S W 14 Section 7 T. 3 R. 39. E W.1	Artesian flow g.p.m. Date Temperature of water Was a chemical analysis ma	4-0 🗆 🕶	+/>-	
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis ma	de? 📋 Ye	s I No	
	(12) WELL LOG: Diameter of well below cas	ing 🗯		
	Depth drilled 394 - ft. Depth of completed well	2001	ft.	
	Formation: Describe by color, character, size of material	and struct	ure and	
	show thickness of aquifers and the kind and nature of the stratum penetrated, with at least one entry for each cha	e material inge of fo	in each rmation.	
	MATERIAL	FROM	TO	
	[[[[]]]] [[]] [[]] [] []			
(3) TYPE OF WORK (check):	- 1 0 0 3 0 1 1 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	5	5	
New Well Deepening Reconditioning Abandon		7	111	
abandonment, describe material and procedure in Item 12.	SAND P Brown Clay Streaks	11/1		
PROPOSED USE (check): (5) TYPE OF WELL	Computed 4th Aver-	44.	///	
Potent Ik Driven	GIAVEL P DOULARIS	7.7	64	
Cable		100	LAX .	
Irrigation 🕏 Test Well 🗆 Other 🗆 Dug 🗀 Bored	Bring Gravel & Doviders -	128	164	
(6) CASING INSTALLED: Threaded □ Welded	Doblgers - (Large)	164	170	
16 "Diam. from - 1 ft. to 394 ft. Gage 14-	Brown /Ay-	170	186	
"Diam. from	Boulders -	186	194	
"Diam. from ft. to ft. Gage	SANGL & JINTEL	174	208	
Diani, Iron	- Clay & Gravel Stratas	208	290	
(7) PERFORATIONS: Perforated? Yes \(\square\) No	1310e (14y -	290	308	
Type of perforator used FACTO14	SANGL P TY A VEL	308	328	
Size of perforations 3//6 in. by 3 in.	Clay & Boulders-	328	344	
perforations from 40 ft. to 394	13 ACK SAND -	344	350	
perforations from ft. to	a Blue (TAY & Grave)	350	365	
perforations from ft. to	t. JANOL P Gravel -	365	387	
perforations from ft. to	a Blue Clay -	385	394	
perforations from ft. to	rt.			
(8) SCREENS: Well screen installed ☐ Yes ☐ No				
Manufacturer's Name				
rpe Model No.				
m. Slot size Set from ft. to		<u>~ 8</u>	1964	
"m. Slot size Set from ft. to	Date well drilling machine moved off of well	Date well drilling machine moved off of well 19		
(9) CONSTRUCTION:	(13) PUMP:			
Well seal-Material used in seal 24 Conductor Bentoni	/e Manufacturer's Name			
well seal—Material used in seal	I ¨			
Diameter of well bore to bottom of seal	Type: H.P.			
Were any loose strata cemented off? Tyes W No Depth	Water Well Contractor's Certification:	į.		
Was a drive shoe used? ☐ Yes Mo	This well was drilled under my jurisdiction ar	i nd this re	enort is	
Was well gravel packed? Yes No Size of gravel: 3/6 X /2	true to the best of my knowledge and belief.			
Gravel placed from Top— tt. to 394 ft.	The Tillian C			
	NAME EN OC Drilling o (Person, firm or corporation) (Type or print)			
Did any strata contain unusable water? Yes No	- Address # 3:3 - LA Grander Citype or prints			
Type of water? Good Depth of strata	- Aduress	<u></u>		
Method of sealing strata off	Drilling Machine Operator's Licepse No			
(10) WATER LEVELS:	Shall han			
Static level 3/2 ft. below land surface Date Dec-/-	[Signed] (Water Welf Contractor)	•	************	
	Contractor's License No. 57 Date 1-2	24	1064	
Artesian pressure Ibs. per square inch Date	_ Contractor a License No	,	19.9.7.	