## filed with the STATE ENGINEER, SALEM, OREGON 9731 Within 30 days from the date of well completion



SIAIL EIAGINEE				
(1) OWNER: SALEM CREGON	(11) LOCATION OF WELL:			
Name Stanley Weishaar	County Union Driller's well n	umber		
Address Rt. 2 La Grande, Ore.	NE 14 SE 14 Section 8 T. JS	R. 3	9 E	W.M.
	Bearing and distance from section or subdivision			
(2) TYPE OF WORK (check):	1988 FT. W. OF SE CORNER		ABONIT	
New Well ∰ Deepening ☐ Reconditioning ☐ Abandon ☐	100 111 30 100		~10 × A &	
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well		13	5/8"
Rotary Z Driven Domestic Industrial Municipal	1. 1.30	below cash	<b>18</b> 280	
Dug    Bored    Irrigation    Test Well   Other	Deput diffice 11. Deput of comp	CTCG WCII		It.
CACING INSTALLED.	Formation: Describe color, texture, grain size and show thickness and nature of each strate			,
CASING INSTALLED: Threaded   Welded   Welded   250   tt. to 280   tt. Gage   250	with at least one entry for each change of form	nation. Re	port each	change
	in position of Static Water Level as drilling pr	1		
" Diam from ft. to ft. Gage	MATERIAL	From	To	SWL
	Topsoil	1 0	12	
PERFORATIONS: Perforated? Yes   No.	Blue sandy clay, Brown	12 25	25 34	
Type of perforator used Factory Peri.	Blue <b>sandy</b> cla <b>y</b> Clay with gravel	311	38	
Size of perforations $1/8!!$ in. by 3 in.		33	<u>56</u>	
3840 perforations from 160 ft. to 280 ft.	Sand, med. to coarse	56		
perforations from tt. to tt.			69 78	<del></del>
perforations from ft. to ft.	Brown sandy cary	69 78	196	
perforations from ft. to ft.	w/gravar	196	214	
perforations from	Sand, some clay	<del>/</del>	214	<del></del>
	Mediun sand & small gray	214	276	
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	The goods aloss gave	21"	_2/9	<del></del>
Manufacturer's Name	Bue sandy clay, some	275	311	
Type Model No	Ziavel	311	322	
Diam Slot size Set from ft. to ft.	Blue clay, some sand Mad. sand. some strayel	322	339	
Diam Slot size Set from ft. to ft.	Blue sandy clay	<del> </del>	327	<del>-</del>
(8) WATER LEVEL: Completed well.		339	<del> </del>	
Static level 16 ft. below land surface Date 11/25/6	Blue clky, sand & grave	3 <b>71</b> 398	398	
sian pressure lbs. per square inch Date		370	-130	·
(0) WELL TESTS. Drawdown is amount water level is				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level		-		
Was a pump test made?  Yes No If yes, by whom?	777-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	<u> </u>	<del></del>	
leld: 80 gal./min. with 20 ft. drawdown after 2 hrs.		ed 11/2		19
	Date well drilling machine moved off of well	11/2//	68	19
" / " " "	<b>Drilling Machine Operator's Certification:</b>			
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under my d			
Artesian flow g.p.m. Date	rials used and information reported aborehowledge and belief.	ve are tr	ue to m	y best
	= 0.40/1	D-4- 77	125	65
Temperature of water 52Was a chemical analysis made? ☐ Yes ( TNo	[Signed] Orilling Machine Operator)	Date 11	,	19QC
(10) CONSTRUCTION:	Drilling Machine Operator's License No.			
Well seal-Material usedCONCRETE				
Depth of seal ft.	Water Well Contractor's Certification:	,		
Diameter of well bore to bottom of seal	This well was drilled under my jurisd		this re	port is
Were any loose strata cemented off? 🗌 Yes 🔊 No Depth	true to the best of my knowledge and beli	E1.		
Was a drive shoe used? 🗌 Yes 🂢 No	(Person, firm/or corporation)	(Type	or print)	
Did any strata contain unusable water?   Yes No	Address 8-6. Box 471 Islan	AC.t.	OLA	,
Type of water? depth of strata	Address O A COLF CALL	·		•••••
Method of sealing strata off	[Signed] To Ellowor	1/R		
Was well gravel packed? ▼ Yes □ No Size of gravel: 3/81	(Water Well Contra	tor)		
Gravel placed from 20 ft. to 280 ft.	Contractor's License No398 Date	1/29		9.68