NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

PWATER WELL REPORT CEIVED STATE OF OREGON MAR 2 7 1974 State Well No. 35

(Please type or print) STATE ENGINEER State Permit No. (Do not write above this line) LEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:
Name COACYT Deck	County UNION Driller's well number
Address Alexandres	14 14 Section 16 T.35 R.39 & W.M.
Cover	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Approx. 1340 W. \$200 5, of NW corner
New Well	of above
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found
Datama & Datama D	
Cable    Jetted	
Dug	Artesian pressure lbs. per square inch. Date
) CASING INSTALLED: Threaded   Welded   25	(12) WELL LOG: Diameter of well below casing 12; the Depth drilled 36 ft. Depth of completed well 353 ft.
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,
, DEPOS A STONE	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
) PERFORATIONS: Perforated? Yes   No.	
Type of perforator used factor a feet	MATERIAL From To SWL
Size of perforations /g in. by / 5 in.	Topsoul 0 5
16 07 perforations from 110 ft. to 150 ft.	Fine sande clay 5 40
2400 perforations from 200 ft. to 260 ft.	Blue sendy clay 40 91
1760 perforations from 290 ft. to 350 ft.	Gravel Fine, clay 91110
(7) SCREENS: Well screen installed?   Yes  No	Small gravel & sand 110 159
Manufacturer's Name	hedren charles sand 191262
Type Model No	Rive & brown clay 262 298
Diam. Slot size Set from ft. to ft.	Smalls ravel & same streaks 290 350
Diam. Slot size Set from ft. to ft.	Clay 2611 1 358 361
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	
" " "	
Bailer test / 50 gal./min. with / 5ft. drawdown after hrs.	
Artesian flow g.p.m.	
perature of water \$30 Depth artesian flow encountered ft.	Work started 12/17 1973 Completed 2/22 1974
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2/22 1974
Well seal-Material used Concrete	Drilling Machine Operator's Certification:
Well sealed from land surface to ft.	This well was constructed under my direct supervision.  Materials used and information reported above are true to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.
Diameter of well bore below sealin.	[Signed] Date 3/28, 1974.
Number of sacks of cement used in well seal 5.5 <	Drilling Machine Operator's License No. 3.7.7
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Excense No
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.  Was a drive shoe used?   Yes  No Plugsft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?   Yes No	Name CARILLE 5 D CLUICK, N C (Person, firm or corporation) (Type or print)
Type of water? depth of strata	Address BOX 613 LAGRANDES ORE.
Method of sealing strata off	MAD Q
Was well gravel packed?    Yes □ No Size of gravel:	[Signed] (Water Well Contractor)
	Contractor's License No. 5/7 Date 3/23 1974
Gravel placed from 20 ft. to 350 ft.	Contractor & Littense No. T Date